

# High-Tech Commodities List for Exportation to Russia and Belarus

## Table of Contents

<b>CATEGORY 0 - NUCLEAR MATERIALS, FACILITIES, AND EQUIPMENT [AND MISCELLANEOUS ITEMS].....</b>	<b>5</b>
<b>0A977 WATER CANNON SYSTEMS FOR RIOT OR CROWD CONTROL, AND “PARTS” AND “COMPONENTS” “SPECIALLY DESIGNED” THEREFOR.....</b>	<b>5</b>
<b>0A978 LAW ENFORCEMENT STRIKING WEAPONS, INCLUDING SAPS, POLICE BATONS, SIDE HANDLE BATONS, TONFAS, SJAMBOKS, AND WHIPS.....</b>	<b>5</b>
<b>0A979 POLICE HELMETS AND SHIELDS; AND “SPECIALLY DESIGNED” “COMPONENTS,” N.E.S. ....</b>	<b>5</b>
<b>0A981 EQUIPMENT DESIGNED FOR THE EXECUTION OF HUMAN BEINGS AS FOLLOWS (SEE LIST OF ITEMS CONTROLLED). ....</b>	<b>5</b>
<b>0A982 LAW ENFORCEMENT RESTRAINT DEVICES, INCLUDING LEG IRONS, SHACKLES, AND HANDCUFFS; STRAIGHT JACKETS; STUN CUFFS; SHOCK BELTS; SHOCK SLEEVES; MULTIPOINT RESTRAINT DEVICES SUCH AS RESTRAINT CHAIRS; AND “SPECIALLY DESIGNED” “PARTS,” “COMPONENTS” AND “ACCESSORIES,” N.E.S. ....</b>	<b>5</b>
<b>0A983 “SPECIALLY DESIGNED” IMPLEMENTS OF TORTURE, INCLUDING THUMBSCREWS, THUMB CUFFS, FINGER CUFFS, SPIKED BATONS, AND “SPECIALLY DESIGNED” “PARTS,” “COMPONENTS” AND “ACCESSORIES,” N.E.S. ....</b>	<b>5</b>
<b>0A998 OIL AND GAS EXPLORATION EQUIPMENT, SOFTWARE, AND DATA, AS FOLLOWS (SEE LIST OF ITEMS CONTROLLED). ....</b>	<b>5</b>
<b>0A999 SPECIFIC PROCESSING EQUIPMENT, AS FOLLOWS (SEE LIST OF ITEMS CONTROLLED). ....</b>	<b>5</b>
<b>0B999 SPECIFIC PROCESSING EQUIPMENT, AS FOLLOWS (SEE LIST OF ITEMS CONTROLLED). ....</b>	<b>6</b>
<b>0D977 “SOFTWARE” “SPECIALLY DESIGNED” FOR THE “DEVELOPMENT,” “PRODUCTION” OR “USE” OF COMMODITIES CONTROLLED BY 0A977. 6</b>	<b>6</b>
<b>0D999 SPECIFIC SOFTWARE, AS FOLLOWS (SEE LIST OF ITEMS CONTROLLED). ....</b>	<b>6</b>
<b>0E977 “TECHNOLOGY” “REQUIRED” FOR THE “DEVELOPMENT” OR “PRODUCTION” OF COMMODITIES CONTROLLED BY 0A977. ....</b>	<b>6</b>
<b>0E982 “TECHNOLOGY” EXCLUSIVELY FOR THE “DEVELOPMENT” OR “PRODUCTION” OF EQUIPMENT CONTROLLED BY 0A982.....</b>	<b>6</b>
<b>CATEGORY 1 - SPECIAL MATERIALS AND RELATED EQUIPMENT .....</b>	<b>7</b>
<b>1A984 CHEMICAL AGENTS, INCLUDING TEAR GAS FORMULATION CONTAINING 1 PERCENT OR LESS OF ORTHOCHLOROBENZALMALONONITRILE (CS), OR 1 PERCENT OR LESS OF CHLOROACETOPHENONE (CN), EXCEPT IN INDIVIDUAL CONTAINERS WITH A NET WEIGHT OF 20 GRAMS OR LESS; LIQUID PEPPER EXCEPT WHEN PACKAGED IN INDIVIDUAL CONTAINERS WITH A NET WEIGHT OF 3 OUNCES (85.05 GRAMS) OR LESS; SMOKE BOMBS; NON-IRRITANT SMOKE FLARES, CANISTERS, GRENADES AND CHARGES; AND OTHER PYROTECHNIC ARTICLES HAVING DUAL MILITARY AND COMMERCIAL USE, AND “PARTS” AND “COMPONENTS” “SPECIALLY DESIGNED” THEREFOR, N.E.S. ....</b>	<b>7</b>
<b>1A985 FINGERPRINTING POWDERS, DYES, AND INKS.....</b>	<b>7</b>
<b>1A995 PROTECTIVE AND DETECTION EQUIPMENT NOT “SPECIALLY DESIGNED” FOR MILITARY USE AND NOT CONTROLLED BY ECCN 1A004 OR ECCN 2B351, AS FOLLOWS (SEE LIST OF ITEMS CONTROLLED), AND “PARTS” AND “COMPONENTS” NOT “SPECIALLY DESIGNED” FOR MILITARY USE AND NOT CONTROLLED BY ECCN 1A004 OR ECCN 2B351 THEREFOR.....</b>	<b>7</b>
<b>1A999 SPECIFIC PROCESSING EQUIPMENT, N.E.S., AS FOLLOWS (SEE LIST OF ITEMS CONTROLLED). ....</b>	<b>7</b>
<b>1B999 SPECIFIC PROCESSING EQUIPMENT, N.E.S., AS FOLLOWS (SEE LIST OF ITEMS CONTROLLED). ....</b>	<b>7</b>
<b>1C990 FIBROUS AND FILAMENTARY MATERIALS, NOT CONTROLLED BY 1C010 OR 1C210, FOR USE IN “COMPOSITE” STRUCTURES AND WITH A SPECIFIC MODULUS OF <math>3.18 \times 10^6</math> M OR GREATER AND A SPECIFIC TENSILE STRENGTH OF <math>7.62 \times 10^4</math> M OR GREATER. ....</b>	<b>8</b>
<b>1C991 VACCINES, IMMUNOTOXINS, MEDICAL PRODUCTS, DIAGNOSTIC AND FOOD TESTING KITS, AS FOLLOWS (SEE LIST OF ITEMS CONTROLLED).....</b>	<b>8</b>
<b>1C992 COMMERCIAL CHARGES AND DEVICES CONTAINING ENERGETIC MATERIALS, N.E.S. AND NITROGEN TRIFLUORIDE IN A GASEOUS STATE (SEE LIST OF ITEMS CONTROLLED). ....</b>	<b>8</b>
<b>1C995 MIXTURES NOT CONTROLLED BY ECCN 1C350, ECCN 1C355 OR ECCN 1C395 THAT CONTAIN CHEMICALS CONTROLLED BY ECCN 1C350 OR ECCN 1C355 AND MEDICAL, ANALYTICAL, DIAGNOSTIC, AND FOOD TESTING KITS NOT CONTROLLED BY ECCN 1C350 OR ECCN 1C395 THAT CONTAIN CHEMICALS CONTROLLED BY ECCN 1C350.D, AS FOLLOWS (SEE LIST OF ITEMS CONTROLLED). ....</b>	<b>9</b>
<b>1C996 HYDRAULIC FLUIDS CONTAINING SYNTHETIC HYDROCARBON OILS, NOT CONTROLLED BY 1C006, HAVING ALL THE FOLLOWING CHARACTERISTICS (SEE LIST OF ITEMS CONTROLLED). ....</b>	<b>10</b>
<b>1C997 AMMONIUM NITRATE, INCLUDING FERTILIZERS AND FERTILIZER BLENDS CONTAINING MORE THAN 15% BY WEIGHT AMMONIUM NITRATE, EXCEPT LIQUID FERTILIZERS (CONTAINING ANY AMOUNT OF AMMONIUM NITRATE) OR DRY FERTILIZERS CONTAINING LESS THAN 15% BY WEIGHT AMMONIUM NITRATE.....</b>	<b>10</b>
<b>1C998 NON-FLUORINATED POLYMERIC SUBSTANCES, NOT CONTROLLED BY 1C008, AS FOLLOWS (SEE LIST OF ITEMS CONTROLLED)..</b>	<b>10</b>
<b>1C999 SPECIFIC MATERIALS, N.E.S., AS FOLLOWS (SEE LIST OF ITEMS CONTROLLED). ....</b>	<b>10</b>
<b>1D999 SPECIFIC SOFTWARE, N.E.S., AS FOLLOWS (SEE LIST OF ITEMS CONTROLLED). ....</b>	<b>11</b>
<b>1E994 “TECHNOLOGY” FOR THE “DEVELOPMENT,” “PRODUCTION,” OR “USE” OF FIBROUS AND FILAMENTARY MATERIALS</b>	

CONTROLLED BY 1C990.....	11
<b>CATEGORY 2 - MATERIALS PROCESSING.....</b>	<b>12</b>
2A983 EXPLOSIVES OR DETONATOR DETECTION EQUIPMENT, BOTH BULK AND TRACE BASED, CONSISTING OF AN AUTOMATED DEVICE, OR COMBINATION OF DEVICES FOR AUTOMATED DECISION MAKING TO DETECT THE PRESENCE OF DIFFERENT TYPES OF EXPLOSIVES, EXPLOSIVE RESIDUE, OR DETONATORS; AND "PARTS" AND "COMPONENTS," N.E.S. ....	12
2A984 CONCEALED OBJECT DETECTION EQUIPMENT OPERATING IN THE FREQUENCY RANGE FROM 30 GHz TO 3000GHz AND HAVING A SPATIAL RESOLUTION OF 0.1 MILLIRADIAN UP TO AND INCLUDING 1 MILLIRADIAN AT A STANDOFF DISTANCE OF 100 METERS; AND "PARTS" AND "COMPONENTS," N.E.S. ....	12
2A991 BEARINGS AND BEARING SYSTEMS NOT CONTROLLED BY 2A001 (SEE LIST OF ITEMS CONTROLLED).....	12
2A992 PIPING, FITTINGS AND VALVES MADE OF, OR LINED WITH STAINLESS, COPPER-NICKEL ALLOY OR OTHER ALLOY STEEL CONTAINING 10% OR MORE NICKEL AND/OR CHROMIUM. ....	13
2A993 PUMPS DESIGNED TO MOVE MOLTEN METALS BY ELECTROMAGNETIC FORCES. ....	13
2A994 PORTABLE ELECTRIC GENERATORS AND "SPECIALLY DESIGNED" "PARTS" AND COMPONENTS." ....	13
2A999 SPECIFIC PROCESSING EQUIPMENT, N.E.S., AS FOLLOWS (SEE LIST OF ITEMS CONTROLLED). ....	13
2B991 NUMERICAL CONTROL UNITS FOR MACHINE TOOLS AND "NUMERICALLY CONTROLLED" MACHINE TOOLS, N.E.S. (SEE LIST OF ITEMS CONTROLLED). ....	14
2B992 NON-"NUMERICALLY CONTROLLED" MACHINE TOOLS FOR GENERATING OPTICAL QUALITY SURFACES, (SEE LIST OF ITEMS CONTROLLED) AND "SPECIALLY DESIGNED" "PARTS" AND "COMPONENTS" THEREFOR. ....	15
2B993 GEARMAKING AND/OR FINISHING MACHINERY NOT CONTROLLED BY 2B003 CAPABLE OF PRODUCING GEARS TO A QUALITY LEVEL OF BETTER THAN AGMA 11. ....	16
2B996 DIMENSIONAL INSPECTION OR MEASURING SYSTEMS OR EQUIPMENT NOT CONTROLLED BY 2B006 OR 2B206, AS FOLLOWS (SEE LIST OF ITEMS CONTROLLED). ....	16
2B997 "ROBOTS" NOT CONTROLLED BY 2B007 OR 2B207 THAT ARE CAPABLE OF EMPLOYING FEEDBACK INFORMATION IN REAL-TIME PROCESSING FROM ONE OR MORE SENSORS TO GENERATE OR MODIFY "PROGRAMS" OR TO GENERATE OR MODIFY NUMERICAL PROGRAM DATA. ....	16
2B998 ASSEMBLIES, CIRCUIT BOARDS OR INSERTS "SPECIALLY DESIGNED" FOR MACHINE TOOLS CONTROLLED BY 2B991, OR FOR EQUIPMENT CONTROLLED BY 2B993, 2B996 OR 2B997. ....	16
2B999 SPECIFIC PROCESSING EQUIPMENT, N.E.S., AS FOLLOWS (SEE LIST OF ITEMS CONTROLLED). ....	16
2D983 "SOFTWARE" "SPECIALLY DESIGNED" OR MODIFIED FOR THE "DEVELOPMENT", "PRODUCTION" OR "USE" OF EQUIPMENT CONTROLLED BY 2A983. ....	17
2D984 "SOFTWARE" "REQUIRED" FOR THE "DEVELOPMENT", "PRODUCTION" OR "USE" OF CONCEALED OBJECT DETECTION EQUIPMENT CONTROLLED BY 2A984. ....	17
2D991 "SOFTWARE" "SPECIALLY DESIGNED" FOR THE "DEVELOPMENT", "PRODUCTION", OR "USE" OF EQUIPMENT CONTROLLED BY 2B991, 2B993, OR 2B996, 2B997, AND 2B998. ....	17
2D992 SPECIFIC "SOFTWARE", AS FOLLOWS (SEE LIST OF ITEMS CONTROLLED). ....	17
2D993 "SOFTWARE" "SPECIALLY DESIGNED" OR MODIFIED FOR THE "DEVELOPMENT," "PRODUCTION," OR "USE" OF ITEMS CONTROLLED BY 2A992 OR 2A993. ....	18
2D994 "SOFTWARE" "SPECIALLY DESIGNED" FOR THE "DEVELOPMENT" OR "PRODUCTION" OF PORTABLE ELECTRIC GENERATORS CONTROLLED BY 2A994. ....	18
2E984 "TECHNOLOGY" "REQUIRED" FOR THE "DEVELOPMENT", "PRODUCTION" OR "USE" OF EQUIPMENT CONTROLLED BY 2A984 OR "REQUIRED" FOR THE "DEVELOPMENT" OF "SOFTWARE" CONTROLLED BY 2D984. ....	18
2E991 "TECHNOLOGY" FOR THE "USE" OF EQUIPMENT CONTROLLED BY 2B991, 2B993, 2B996, OR 2B997. ....	18
2E993 "TECHNOLOGY" ACCORDING TO THE GENERAL TECHNOLOGY NOTE FOR THE "USE" OF EQUIPMENT CONTROLLED BY 2A992 OR 2A993. ....	18
2E994 "TECHNOLOGY" FOR THE "USE" OF PORTABLE ELECTRIC GENERATORS CONTROLLED BY 2A994. ....	18
<b>CATEGORY 3 - ELECTRONICS.....</b>	<b>19</b>
3A991 ELECTRONIC DEVICES AND COMPONENTS. ....	19
3A992 GENERAL PURPOSE "ELECTRONIC ASSEMBLIES", MODULES AND EQUIPMENT. ....	22
3A999 SPECIFIC PROCESSING EQUIPMENT, OTHER THAN THOSE SPECIFIED IN THE CML OR IN REGULATION (EU) 2021/821, AS FOLLOWS:.....	23
3B991 EQUIPMENT FOR THE MANUFACTURE OF ELECTRONIC COMPONENTS OR MATERIALS, AS FOLLOWS AND SPECIALLY DESIGNED COMPONENTS AND ACCESSORIES THEREFOR. ....	23
3B992 EQUIPMENT FOR THE INSPECTION OR TESTING OF ELECTRONIC COMPONENTS AND MATERIALS, AND SPECIALLY DESIGNED COMPONENTS AND ACCESSORIES THEREFOR. ....	29
3C991 POSITIVE RESISTS DESIGNED FOR SEMICONDUCTOR LITHOGRAPHY SPECIALLY ADJUSTED (OPTIMISED) FOR USE AT WAVELENGTHS BETWEEN 370 AND 193 NM. ....	31
3D991 "SOFTWARE" SPECIALLY DESIGNED FOR THE "DEVELOPMENT", "PRODUCTION", OR "USE" OF ELECTRONIC DEVICES OR COMPONENTS CONTROLLED BY 3A991, GENERAL PURPOSE ELECTRONIC EQUIPMENT CONTROLLED BY 3A992, OR MANUFACTURING AND TEST EQUIPMENT CONTROLLED BY 3B991 AND 3B992; OR "SOFTWARE" SPECIALLY DESIGNED FOR THE "USE" OF EQUIPMENT CONTROLLED BY 3B001.G AND 3B001.H. ....	31

3E991	“TECHNOLOGY” FOR THE “DEVELOPMENT”, “PRODUCTION” OR “USE” OF ELECTRONIC DEVICES OR COMPONENTS CONTROLLED BY 3A991, GENERAL PURPOSE ELECTRONIC EQUIPMENT CONTROLLED BY 3A992, OR MANUFACTURING AND TEST EQUIPMENT CONTROLLED BY 3B991 OR 3B992, OR MATERIALS CONTROLLED BY 3C991. ....	31
<b>CATEGORY 4 – COMPUTERS .....</b>		<b>32</b>
4A994	COMPUTERS, “ELECTRONIC ASSEMBLIES” AND RELATED EQUIPMENT, NOT CONTROLLED BY 4A001 OR 4A003, AND SPECIALLY DESIGNED COMPONENTS THEREFOR. ....	32
4D993	“PROGRAM” PROOF AND VALIDATION “SOFTWARE”, “SOFTWARE” ALLOWING THE AUTOMATIC GENERATION OF “SOURCE CODES”, AND OPERATING SYSTEM “SOFTWARE” THAT ARE SPECIALLY DESIGNED FOR “REAL-TIME PROCESSING” EQUIPMENT. ....	33
4D994	“SOFTWARE” OTHER THAN THAT CONTROLLED IN 4D001 SPECIALLY DESIGNED OR MODIFIED FOR THE “DEVELOPMENT”, “PRODUCTION” OR “USE” OF EQUIPMENT CONTROLLED BY 4A101, 4A994. ....	34
4E992	“TECHNOLOGY” FOR THE “DEVELOPMENT”, “PRODUCTION” OR “USE” OF EQUIPMENT CONTROLLED BY 4A994, OR “SOFTWARE” CONTROLLED BY 4D993 OR 4D994. ....	34
4E993	“TECHNOLOGY” FOR THE “DEVELOPMENT” OR “PRODUCTION” OF EQUIPMENT DESIGNED FOR ‘MULTI-DATA-STREAM PROCESSING’. ....	34
<b>CATEGORY 5. PART 1 – TELECOMMUNICATIONS .....</b>		<b>35</b>
5A991	TELECOMMUNICATION EQUIPMENT. ....	35
5C991	PREFORMS OF GLASS OR OF ANY OTHER MATERIAL OPTIMISED FOR THE MANUFACTURE OF OPTICAL FIBRES CONTROLLED BY 5A991. 40	
5D991	“SOFTWARE” SPECIALLY DESIGNED OR MODIFIED FOR THE “DEVELOPMENT”, “PRODUCTION” OR “USE” OF EQUIPMENT CONTROLLED BY 5A991 AND 5B991, AND DYNAMIC ADAPTIVE ROUTING SOFTWARE AS DESCRIBED AS FOLLOWS: ....	40
5E991	“TECHNOLOGY” FOR THE “DEVELOPMENT”, “PRODUCTION” OR “USE” OF EQUIPMENT CONTROLLED BY 5A991 OR 5B991, OR “SOFTWARE” CONTROLLED BY 5D991, AND OTHER “TECHNOLOGIES” AS FOLLOWS: ....	40
<b>CATEGORY 5. PART 2 - INFORMATION SECURITY .....</b>		<b>41</b>
5A992	EQUIPMENT AS FOLLOWS: ....	41
5D992	“INFORMATION SECURITY” “SOFTWARE” AS FOLLOWS: ....	41
5E992	“INFORMATION SECURITY” “TECHNOLOGY” ACCORDING TO THE GENERAL TECHNOLOGY NOTE, AS FOLLOWS: ....	41
<b>CATEGORY 6 – SENSORS AND LASERS .....</b>		<b>42</b>
6A991	MARINE OR TERRESTRIAL ACOUSTIC EQUIPMENT, CAPABLE OF DETECTING OR LOCATING UNDERWATER OBJECTS OR FEATURES OR POSITIONING SURFACE VESSELS OR UNDERWATER VEHICLES; AND SPECIALLY DESIGNED COMPONENTS, OTHER THAN THOSE SPECIFIED IN THE CML OR IN REGULATION (EU) 2021/821. ....	42
6A992	OPTICAL SENSORS AS FOLLOWS: ....	42
6A993	CAMERAS AS FOLLOWS: ....	42
6A994	OPTICS AS FOLLOWS: ....	42
6A995	“LASERS” AS FOLLOWS: ....	43
6A996	“MAGNETOMETERS”, “SUPERCONDUCTIVE” ELECTROMAGNETIC SENSORS, AND SPECIALLY DESIGNED COMPONENTS THEREFOR, AS FOLLOWS: ....	45
6A997	GRAVITY METERS (GRAVIMETERS) FOR GROUND USE, OTHER THAN THOSE SPECIFIED IN THE CML OR IN REGULATION (EU) 2021/821, AS FOLLOWS: ....	46
6A998	RADAR SYSTEMS, EQUIPMENT AND MAJOR COMPONENTS, OTHER THAN THOSE SPECIFIED IN THE CML OR IN REGULATION (EU) 2021/821, AND SPECIALLY DESIGNED COMPONENTS THEREFOR, AS FOLLOWS: ....	46
6A999	SPECIFIC PROCESSING EQUIPMENT, AS FOLLOWS: ....	47
6B995	EQUIPMENT, INCLUDING TOOLS, DIES, FIXTURES OR GAUGES, AND OTHER SPECIALLY DESIGNED COMPONENTS AND ACCESSORIES THEREFOR, SPECIALLY DESIGNED OR MODIFIED FOR ANY OF THE FOLLOWING: ....	47
6C992	OPTICAL SENSING FIBRES THAT ARE MODIFIED STRUCTURALLY TO HAVE A “BEAT LENGTH” OF LESS THAN 500 MM (HIGH BIREFRINGENCE) OR OPTICAL SENSOR MATERIALS NOT DESCRIBED IN 6C002.B <sup>1</sup> AND HAVING A ZINC CONTENT OF EQUAL TO OR MORE THAN 6% BY “MOLE FRACTION.” ....	47
6C994	OPTICAL MATERIALS, AS FOLLOWS: ....	47
6D991	“SOFTWARE”, OTHER THAN THOSE SPECIFIED IN THE CML OR IN REGULATION (EU) 2021/821, SPECIALLY DESIGNED FOR THE “DEVELOPMENT”, “PRODUCTION”, OR “USE” OF GOODS CONTROLLED BY 6A002, 6A003, 6A991, 6A996, 6A997, OR 6A998. ....	48
6D992	“SOFTWARE” SPECIALLY DESIGNED FOR THE “DEVELOPMENT” OR “PRODUCTION” OF EQUIPMENT CONTROLLED BY 6A992, 6A994, OR 6A995. ....	48
6D993	OTHER “SOFTWARE”, AS FOLLOWS: ....	48
6E991	“TECHNOLOGY” FOR THE “DEVELOPMENT”, “PRODUCTION” OR “USE” OF EQUIPMENT CONTROLLED BY 6A991, 6A996, 6A997, 6A998 OR 6A999. ....	48
6E992	“TECHNOLOGY” FOR THE “DEVELOPMENT” OR “PRODUCTION” OF EQUIPMENT, MATERIALS OR “SOFTWARE” CONTROLLED BY 6A992, 6A994, OR 6A995, 6B995, 6C992, 6C994, OR 6D993. ....	48
6E993	OTHER “TECHNOLOGY” AS FOLLOWS: ....	48

**CATEGORY 7 – NAVIGATION AND AVIONICS..... 50**

- 7A994 AIRBORNE COMMUNICATION EQUIPMENT, ALL "AIRCRAFT" INERTIAL NAVIGATION SYSTEMS, AND OTHER AVIONIC EQUIPMENT, INCLUDING COMPONENTS, OTHER THAN THOSE SPECIFIED IN THE CML OR IN REGULATION (EU) 2021/821. .... 50
- 7B994 OTHER EQUIPMENT SPECIALLY DESIGNED FOR THE TEST, INSPECTION, OR "PRODUCTION" OF NAVIGATION AND AVIONICS EQUIPMENT. 50
- 7D994 "SOFTWARE", OTHER THAN SPECIFIED IN THE CML OR IN REGULATION (EU) 2021/821, FOR THE "DEVELOPMENT", "PRODUCTION", OR "USE" OF NAVIGATION, AIRBORNE COMMUNICATION AND OTHER AVIONICS..... 50
- 7E994 "TECHNOLOGY", OTHER THAN SPECIFIED IN THE CML OR IN REGULATION (EU) 2021/821, FOR THE "DEVELOPMENT", "PRODUCTION" OR "USE" OF NAVIGATION, AIRBORNE COMMUNICATION, AND OTHER AVIONICS EQUIPMENT. .... 50

**CATEGORY 8 – MARINE..... 51**

- 8A992 VESSELS, MARINE SYSTEMS OR EQUIPMENT, AND SPECIALLY DESIGNED COMPONENTS THEREFOR, COMPONENTS AND ACCESSORIES AS FOLLOWS: ..... 51
- 8D992 "SOFTWARE" SPECIALLY DESIGNED OR MODIFIED FOR THE "DEVELOPMENT", "PRODUCTION" OR "USE" OF EQUIPMENT CONTROLLED BY 8A992. .... 52
- 8D999 "SOFTWARE" SPECIALLY DESIGNED FOR THE OPERATION OF UNMANNED SUBMERSIBLE VEHICLES USED IN THE OIL AND GAS INDUSTRY. .... 52
- 8E992 "TECHNOLOGY" FOR THE "DEVELOPMENT", "PRODUCTION" OR "USE" OF EQUIPMENT CONTROLLED BY 8A992. .... 52

**CATEGORY 9 – AEROSPACE AND PROPULSION..... 53**

- 9A990 DIESEL ENGINES, AND TRACTORS AND SPECIALLY DESIGNED COMPONENTS THEREFOR, OTHER THAN THOSE SPECIFIED IN THE CML OR IN REGULATION (EU) 2021/821. .... 53
- 9A991 GAS TURBINE ENGINES AND COMPONENTS, OTHER THAN THOSE SPECIFIED IN THE CML OR IN REGULATION (EU) 2021/821. 53
- 9A992 COMPLETE CANOPIES, HARNESSSES, AND PLATFORMS AND ELECTRONIC RELEASE MECHANISMS THEREFOR, EXCEPT SUCH TYPES AS ARE IN NORMAL SPORTING USE..... 53
- 9B990 VIBRATION TEST EQUIPMENT AND SPECIALLY DESIGNED COMPONENTS, OTHER THAN THOSE SPECIFIED IN THE CML OR IN REGULATION (EU) 2021/821. .... 53
- 9B991 SPECIALLY DESIGNED "EQUIPMENT", TOOLING OR FIXTURES FOR MANUFACTURING OR MEASURING GAS TURBINE BLADES, VANES OR TIP SHROUD CASTINGS, AS FOLLOWS: ..... 53
- 9D990 "SOFTWARE", OTHER THAN THOSE SPECIFIED IN THE CML OR IN REGULATION (EU) 2021/821, FOR THE "DEVELOPMENT" OR "PRODUCTION" OF EQUIPMENT CONTROLLED BY 9A990 OR 9B990 ..... 54
- 9D991 "SOFTWARE", FOR THE "DEVELOPMENT" OR "PRODUCTION" OF EQUIPMENT CONTROLLED BY 9A991 OR 9B991. .... 54
- 9E990 "TECHNOLOGY", OTHER THAN THOSE SPECIFIED IN THE CML OR IN REGULATION (EU) 2021/821, FOR THE "DEVELOPMENT" OR "PRODUCTION" OR "USE" OF EQUIPMENT CONTROLLED BY 9A990 OR 9B990 ..... 54
- 9E991 "TECHNOLOGY", FOR THE "DEVELOPMENT", "PRODUCTION" OR "USE" OF EQUIPMENT CONTROLLED BY 9A991 OR 9B991.... 54
- 9E993 OTHER "TECHNOLOGY", NOT DESCRIBED BY 9E003, AS FOLLOWS: ..... 54

**CATEGORY 0 - NUCLEAR MATERIALS, FACILITIES, AND  
EQUIPMENT [AND MISCELLANEOUS ITEMS]**

A. Systems, Equipment and Components

0A977 Water cannon systems for riot or crowd control, and “parts” and “components” “specially designed” therefor.

*Note:* 0A977 water cannon systems include, for example: vehicles or fixed stations equipped with remotely operated water cannon that are designed to protect the operator from an outside riot with features such as armor, shatter resistant windows, metal screens, bull-bars, or run-flat tires. Components “specially designed” for water cannons may include, for example: deck gun water nozzles, pumps, reservoirs, cameras, and lights that are hardened or shielded against projectiles, elevating masts for those items, and teleoperation systems for those items.

0A978 Law enforcement striking weapons, including saps, police batons, side handle batons, tonfas, sjamboks, and whips.

0A979 Police helmets and shields; and “specially designed” “components,” n.e.s.

0A981 Equipment designed for the execution of human beings as follows (see List of Items Controlled).

- a. Gallows and guillotines.
- b. Electric chairs for the purpose of executing human beings.
- c. Air tight vaults designed for the execution of human beings by the administration of a lethal gas or substance.
- d. Automatic drug injection systems designed for the execution of human beings by administration of a lethal substance.

0A982 Law enforcement restraint devices, including leg irons, shackles, and handcuffs; straight jackets; stun cuffs; shock belts; shock sleeves; multipoint restraint devices such as restraint chairs; and “specially designed” “parts,” “components” and “accessories,” n.e.s.

*Note to ECCN 0A982. This ECCN applies to restraint devices used in law enforcement activities. It does not apply to medical devices that are equipped to restrain patient movement during medical procedures. It does not apply to devices that confine memory impaired patients to appropriate medical facilities. It does not apply to safety equipment such as safety belts or child automobile safety seats.*

0A983 “Specially designed” implements of torture, including thumbscrews, thumbcuffs, fingercuffs, spiked batons, and “specially designed” “parts,” “components” and “accessories,” n.e.s.

0A998 Oil and gas exploration equipment, software, and data, as follows (see List of Items Controlled).

- a. Oil and gas exploration data, e.g., seismic analysis data.
- b. Hydraulic fracturing items, as follows:
  - b.1. Hydraulic fracturing design and analysis software and data.
  - b.2. Hydraulic fracturing ‘proppant,’ ‘fracking fluid,’ and chemical additives therefor.

*Technical Note: A ‘proppant’ is a solid material, typically treated sand or man-made ceramic materials, designed to keep an induced hydraulic fracture open, during or following a fracturing treatment. It is added to a ‘fracking fluid’ which may vary in composition depending on the type of fracturing used, and can be gel, foam or slickwater-based.*

c.1. High pressure pumps.

0A999 Specific processing equipment, as follows (see List of Items Controlled).

- a. Ring Magnets;
- b. [Reserved]

B. TEST, INSPECTION AND “PRODUCTION EQUIPMENT”

0B999 Specific processing equipment, as follows (see List of Items Controlled).

- a. Hot cells;
- b. Glove boxes suitable for use with radioactive materials.

C. “MATERIALS”

Reserved

D. “SOFTWARE”

0D977 “Software” “specially designed” for the “development,” “production” or “use” of commodities controlled by 0A977.

0D999 Specific software, as follows (see List of Items Controlled).

- a. Software for neutronic calculations/modeling;
- b. Software for radiation transport calculations/modeling;
- c. Software for hydrodynamic calculations/modeling.

E. “TECHNOLOGY”

0E977 “Technology” “required” for the “development” or “production” of commodities controlled by 0A977.

0E982 “Technology” exclusively for the “development” or “production” of equipment controlled by 0A982.

## CATEGORY 1 - SPECIAL MATERIALS AND RELATED EQUIPMENT

### A. Systems, Equipment and Components

1A984 Chemical agents, including tear gas formulation containing 1 percent or less of orthochlorobenzalmalononitrile (CS), or 1 percent or less of chloroacetophenone (CN), except in individual containers with a net weight of 20 grams or less; liquid pepper except when packaged in individual containers with a net weight of 3 ounces (85.05 grams) or less; smoke bombs; non-irritant smoke flares, canisters, grenades and charges; and other pyrotechnic articles having dual military and commercial use, and “parts” and “components” “specially designed” therefor, n.e.s.

1A985 Fingerprinting powders, dyes, and inks.

1A995 Protective and detection equipment not “specially designed” for military use and not controlled by ECCN 1A004 or ECCN 2B351, as follows (see List of Items Controlled), and “parts” and “components” not “specially designed” for military use and not controlled by ECCN 1A004 or ECCN 2B351 therefor.

a. Personal radiation monitoring dosimeters;

b. Equipment limited by design or function to protect against hazards specific to civil industries, such as mining, quarrying, agriculture, pharmaceuticals, medical, veterinary, environmental, waste management, or to the food industry.

*Note: This entry (1A995) does not control items for protection against chemical or biological agents that are consumer goods, packaged for retail sale or personal use, or medical products, such as latex exam gloves, latex surgical gloves, liquid disinfectant soap, disposable surgical drapes, surgical gowns, surgical foot covers, and surgical masks. Such items are classified as EAR99.*

1A999 Specific processing equipment, n.e.s., as follows (see List of Items Controlled).

a. Radiation detection, monitoring and measurement equipment, n.e.s.;

b. Radiographic detection equipment such as x-ray converters, and storage phosphor image plates.

### B. TEST, INSPECTION AND “PRODUCTION EQUIPMENT”

1B999 Specific processing equipment, n.e.s., as follows (see List of Items Controlled).

a. Electrolytic cells for fluorine production, n.e.s.;

b. Particle accelerators;

c. Industrial process control hardware/systems designed for power industries, n.e.s.;

d. Freon and chilled water cooling systems capable of continuous cooling duties of 100,000 BTU/hr (29.3kW) or greater;

e. Equipment for the production of structural composites, fibers, prepregs and preforms, n.e.s.

### C. “MATERIALS”

#### *Technical Note:*

*Metals and alloys: Unless provision to the contrary is made, the words “metals” and “alloys” in 1C001 to 1C011 cover crude and semi-fabricated forms, as follows:*

*Crude forms: Anodes, balls, bars (including notched bars and wire bars), billets, blocks, blooms, brickets, cakes, cathodes, crystals, cubes, dice, grains, granules, ingots, lumps, pellets, pigs, powder, rondelles, shot, slabs, slugs,*

sponge, sticks;

*Semi-fabricated forms (whether or not coated, plated, drilled or punched):*

- a. *Wrought or worked materials fabricated by rolling, drawing, extruding, forging, impact extruding, pressing, graining, atomizing, and grinding, i.e.: angles, channels, circles, discs, dust, flakes, foils and leaf, forging, plate, powder, pressings and stampings, ribbons, rings, rods (including bare welding rods, wire rods, and rolled wire), sections, shapes, sheets, strip, pipe and tubes (including tube rounds, squares, and hollows), drawn or extruded wire;*
- b. *Cast material produced by casting in sand, die, metal, plaster or other types of molds, including high pressure castings, sintered forms, and forms made by powder metallurgy.*

*The object of the control should not be defeated by the export of non-listed forms alleged to be finished products but representing in reality crude forms or semi-fabricated forms.*

1C990 Fibrous and filamentary materials, not controlled by 1C010 or 1C210, for use in “composite” structures and with a specific modulus of  $3.18 \times 10^6$  m or greater and a specific tensile strength of  $7.62 \times 10^4$  m or greater.

1C991 Vaccines, immunotoxins, medical products, diagnostic and food testing kits, as follows (see List of Items controlled).

*Technical Note: For purposes of the controls described in this ECCN, ‘toxins’ refers to those toxins, or their subunits, controlled under ECCN 1C351.d.*

- a. Vaccines containing, or designed for use against, items controlled by ECCN 1C351, 1C353 or 1C354;
- b. Immunotoxins containing items controlled by 1C351.d;
- c. Medical products that contain any of the following:
  - c.1. Toxins controlled by ECCN 1C351.d (*except for* botulinum toxins controlled by ECCN 1C351.d.3, conotoxins controlled by ECCN 1C351.d.6, or items controlled for CW reasons under ECCN 1C351.d.11 or .d.12); *or*
  - c.2. Genetically modified organisms or genetic elements controlled by ECCN 1C353.a.3 (except for those that contain, or code for, botulinum toxins controlled by ECCN 1C351.d.3 or conotoxins controlled by ECCN 1C351.d.6);
- d. Medical products not controlled by 1C991.c that contain any of the following:
  - d.1. Botulinum toxins controlled by ECCN 1C351.d.3;
  - d.2. Conotoxins controlled by ECCN 1C351.d.6; *or*
  - d.3. Genetically modified organisms or genetic elements controlled by ECCN 1C353.a.3 that contain, or code for, botulinum toxins controlled by ECCN 1C351.d.3 or conotoxins controlled by ECCN 1C351.d.6;
- e. Diagnostic and food testing kits containing items controlled by ECCN 1C351.d (except for items controlled for CW reasons under ECCN 1C351.d.11 or .d.12).

1C992 Commercial charges and devices containing energetic materials, n.e.s. and nitrogen trifluoride in a gaseous state (see List of Items Controlled).

- a. Shaped charges “specially designed” for oil well operations, utilizing one charge functioning along a single axis, that upon detonation produce a hole, and
  - a.1. Contain any formulation of controlled materials;
  - a.2. Have only a uniform shaped conical liner with an included angle of 90 degrees or less;
  - a.3. Contain more than 0.010 kg but less than or equal to 0.090 kg of controlled materials; and
  - a.4. Have a diameter not exceeding 4.5 inches;



- b. Shaped charges “specially designed” for oil well operations containing less than or equal to 0.010 kg of controlled materials;
- c. Detonation cord or shock tubes containing less than or equal to 0.064 kg per meter (300 grains per foot) of controlled materials;
- d. Cartridge power devices, that contain less than or equal to 0.70 kg of controlled materials in the deflagration material;
- e. Detonators (electric or nonelectric) and assemblies thereof, that contain less than or equal to 0.01 kg of controlled materials;
- f. Igniters, that contain less than or equal to 0.01 kg of controlled materials;
- g. Oil well cartridges, that contain less than or equal to 0.015 kg of controlled energetic materials;
- h. Commercial cast or pressed boosters containing less than or equal to 1.0 kg of controlled materials;
- i. Commercial prefabricated slurries and emulsions containing less than or equal to 10.0 kg and less than or equal to thirty-five percent by weight of USML controlled materials;
- j. Cutters and severing tools containing less than or equal to 3.5 kg of controlled materials;
- k. Pyrotechnic devices when designed exclusively for commercial purposes (e.g., theatrical stages, motion picture special effects, and fireworks displays) and containing less than or equal to 3.0 kg of controlled materials; or
- l. Other commercial explosive devices and charges not controlled by 1C992.a through .k containing less than or equal to 1.0 kg of controlled materials.

*Note: 1C992.l includes automotive safety devices; extinguishing systems; cartridges for riveting guns; explosive charges for agricultural, oil and gas operations, sporting goods, commercial mining, or public works purposes; and delay tubes used in the assembly of commercial explosive devices.*

- m. Nitrogen trifluoride (NF<sub>3</sub>) in a gaseous state.

1C995 Mixtures not controlled by ECCN 1C350, ECCN 1C355 or ECCN 1C395 that contain chemicals controlled by ECCN 1C350 or ECCN 1C355 and medical, analytical, diagnostic, and foodtesting kits not controlled by ECCN 1C350 or ECCN 1C395 that contain chemicals controlled by ECCN 1C350.d, as follows (see List of Items Controlled).

- a. Mixtures containing the following concentrations of precursor chemicals controlled by ECCN 1C350 (For controls on other mixtures containing these chemicals, see Notes 1 and 2 in the Related Controls paragraph of this ECCN.):
  - a.1. Mixtures containing 10 percent or less, by weight, of any single CWC Schedule 2 chemical controlled by ECCN 1C350.b;
  - a.2. Mixtures containing less than 30 percent, by weight, of:
    - a.2.a. Any single CWC Schedule 3 chemical controlled by ECCN 1C350.c; or
    - a.2.b. Any single precursor chemical controlled by ECCN 1C350.d.
- b. Mixtures containing the following concentrations of toxic or precursor chemicals controlled by ECCN 1C355 (For controls on other mixtures containing these chemicals, see Note 3 in the Related Controls paragraph of this ECCN.):
  - b.1. Mixtures containing the following concentrations of CWC Schedule 2 chemicals controlled by ECCN 1C355.a:

- b.1.a. Mixtures containing 1 percent or less, by weight, of any single CWC Schedule 2 chemical controlled by ECCN 1C355.a.1 (i.e., mixtures containing PFIB); or
- b.1.b. Mixtures containing 10 percent or less, by weight, of any single CWC Schedule 2 chemical controlled by 1C355.a.2;
- b.2. Mixtures containing less than 30 percent, by weight, of any single CWC Schedule 3 chemical controlled by ECCN 1C355.b.
- c. “Medical, analytical, diagnostic, and food testing kits” (as defined in the Related Definitions for this ECCN) that contain precursor chemicals controlled by ECCN 1C350.d in an amount not exceeding 300 grams per chemical. (For controls on other such test kits containing these and other controlled chemicals, see Note 4 in the Related Controls paragraph of this ECCN.)

1C996 Hydraulic fluids containing synthetic hydrocarbon oils, not controlled by 1C006, having all the following characteristics (see List of Items Controlled).

- a. A flash point exceeding 477 K (204 °C);
- b. A pour point at 239 K (-34 °C) or less;
- c. A viscosity index of 75 or more; *and*
- d. A thermal stability at 616 K (343 °C).

1C997 Ammonium nitrate, including fertilizers and fertilizer blends containing more than 15% by weight ammonium nitrate, except liquid fertilizers (containing any amount of ammonium nitrate) or dry fertilizers containing less than 15% by weight ammonium nitrate.

1C998 Non-fluorinated polymeric substances, not controlled by 1C008, as follows (see List of Items Controlled).

- a. Polyarylene ether ketones, as follows:
  - a.1. Polyether ether ketone (PEEK);
  - a.2. Polyether ketone ketone (PEKK);
  - a.3. Polyether ketone (PEK);
  - a.4. Polyether ketone ether ketone ketone (PEKEKK);
- b. [Reserved].

1C999 Specific materials, n.e.s., as follows (see List of Items Controlled).

- a. Hardened steel and tungsten carbide precision ball bearings (3mm or greater diameter);
- b. 304 and 316 stainless steel plate, n.e.s.;
- c. Monel plate;
- d. Tributyl phosphate;
- e. Nitric acid in concentrations of 20 weight percent or greater;
- f. Fluorine;
- g. Alpha-emitting radionuclides, n.e.s.

#### D. “SOFTWARE”

1D999 Specific software, n.e.s., as follows (see List of Items Controlled).

- a. Software “specially designed” for industrial process control hardware/systems controlled by 1B999, n.e.s.;
- b. Software “specially designed” for equipment for the production of structural composites, fibers, prepregs and preforms controlled by 1B999, n.e.s.

E. “TECHNOLOGY”

1E994 “Technology” for the “development”, “production”, or “use” of fibrous and filamentary materials controlled by 1C990.

## **CATEGORY 2 - MATERIALS PROCESSING**

### **A. “END ITEMS,” “EQUIPMENT,” “ACCESSORIES,” “ATTACHMENTS,” “PARTS,” “COMPONENTS,” AND “SYSTEMS”**

2A983 Explosives or detonator detection equipment, both bulk and trace based, consisting of an automated device, or combination of devices for automated decision making to detect the presence of different types of explosives, explosive residue, or detonators; and “parts” and “components,” n.e.s.

*Note: Explosives or detonation detection equipment in 2A983 includes equipment for screening people, documents, baggage, other personal effects, cargo and/or mail.*

a. Explosives detection equipment for automated decision making to detect and identify bulk explosives utilizing, but not limited to, x-ray (e.g., computed tomography, dual energy, or coherent scattering), nuclear (e.g., thermal neutron analysis, pulse fast neutron analysis, pulse fast neutron transmission spectroscopy, and gamma resonance absorption), or electromagnetic techniques (e.g., quadrupole resonance and dielectrometry).

b. [RESERVED]

c. Detonator detection equipment for automated decision making to detect and identify initiation devices (e.g. detonators, blasting caps) utilizing, but not limited to, x-ray (e.g. dual energy or computed tomography) or electromagnetic techniques.

2A984 Concealed object detection equipment operating in the frequency range from 30 GHz to 3000GHz and having a spatial resolution of 0.1 milliradian up to and including 1 milliradian at a standoff distance of 100 meters; and “parts” and “components,” n.e.s.

*Note: Concealed object detection equipment includes but is not limited to equipment for screening people, documents, baggage, other personal effects, cargo and/or mail.*

*Technical Note: The range of frequencies span what is generally considered as the millimeter-wave, submillimeter-wave and terahertz frequency regions.*

2A991 Bearings and bearing systems not controlled by 2A001 (see List of Items Controlled).

*Related Definitions:* (1) (a) DN is the product of the bearing bore diameter in mm and the bearing rotational velocity in rpm. (b) Operating temperatures include those temperatures obtained when a gasturbine engine has stopped after operation. (2) Annular Bearing Engineers Committee (ABEC); American National Standards Institute (ANSI); Anti-Friction Bearing Manufacturers Association (AFBMA)

a. Ball bearings or Solid ball bearings, having tolerances specified by the manufacturer in accordance with ABEC 7, ABEC 7P, or ABEC 7T or ISO Standard Class 4 or better (or equivalents) and having any of the following characteristics.

a.1. Manufactured for use at operating temperatures above 573 K (300 °C) either by using special materials or by special heat treatment; or

a.2. With lubricating elements or “part” or “component” modifications that, according to the manufacturer's specifications, are “specially designed” to enable the bearings to operate at speeds exceeding 2.3 million DN.

b. Solid tapered roller bearings, having tolerances specified by the manufacturer in accordance with ANSI/AFBMA Class 00 (inch) or Class A (metric) or better (or equivalents) and having either of the following characteristics.

b.1. With lubricating elements or “part” or “component” modifications that, according to the manufacturer's specifications, are “specially designed” to enable the bearings to operate at

speeds exceeding 2.3 million DN; *or*

- b.2. Manufactured for use at operating temperatures below 219 K (-54 °C) or above 423 K (150 °C).
- c. Gas-lubricated foil bearing manufactured for use at operating temperatures of 561 K (288 °C) or higher and a unit load capacity exceeding 1 MPa.
- d. Active magnetic bearing systems.
- e. Fabric-lined self-aligning or fabric-lined journal sliding bearings manufactured for use at operating temperatures below 219 K (-54 °C) or above 423 K (150 °C).

2A992 Piping, fittings and valves made of, or lined with stainless, copper-nickel alloy or other alloy steel containing 10% or more nickel and/or chromium.

- a. Pressure tube, pipe, and fittings of 200 mm (8 in.) or more inside diameter, and suitable for operation at pressures of 3.4 MPa (500 psi) or greater;
- b. Pipe valves having all of the following characteristics that are not controlled by ECCN 2B350.g:
  - b.1. A pipe size connection of 200 mm (8 in.) or more inside diameter; *and*
  - b.2. Rated at 10.3 MPa (1,500 psi) or more.

2A993 Pumps designed to move molten metals by electromagnetic forces.

2A994 Portable electric generators and “specially designed” “parts” and components.”

*Related Definitions:* ‘Portable electric generators’ – The generators that are in 2A994 are portable – 5,000 lbs. or less on wheels or transportable in a 2½ ton truck without a “special set up requirement.

2A999 Specific processing equipment, n.e.s., as follows (see List of Items Controlled).

- a. Bellows sealed valves;
- b. [RESERVED].

## B. “TEST,” “INSPECTION” AND “PRODUCTION EQUIPMENT”

### *TECHNICAL NOTES FOR 2B991 TO 2B999:*

1. *Secondary parallel contouring axes, (e.g., the w-axis on horizontal boring mills or a secondary rotary axis the center line of which is parallel to the primary rotary axis) are not counted in the total number of contouring axes. Rotary axes need not rotate over 360°. A rotary axis can be driven by a linear device (e.g., a screw or a rack-and-pinion).*
2. *The number of axes which can be coordinated simultaneously for “contouring control” is the number of axes along or around which, during processing of the workpiece, simultaneous and interrelated motions are performed between the workpiece and a tool. This does not include any additional axes along or around which other relative motions within the machine are performed, such as:*
  - 2.a. *Wheel-dressing systems in grinding machines;*
  - 2.b. *Parallel rotary axes designed for mounting of separate workpieces;*
  - 2.c. *Co-linear rotary axes designed for manipulating the same workpiece by holding it in a chuck from different ends.*
3. *Axis nomenclature shall be in accordance with International Standard ISO 841:2001, Industrial automation systems and integration - Numerical control of machines - Coordinate system and motion nomenclature.*
4. *A “tilting spindle” is counted as a rotary axis.*

5. *‘Stated “unidirectional positioning repeatability” ’ may be used for each specific machine model as an alternative to individual machine tests, and is determined as follows:*
  - 5.a. *Select five machines of a model to be evaluated;*
  - 5.b. *Measure the linear axis repeatability ( $R_{\uparrow}, R_{\downarrow}$ ) according to ISO 230-2:2014 and evaluate "unidirectional positioning repeatability" for each axis of each of the five machines;*
  - 5.c. *Determine the arithmetic mean value of the "unidirectional positioning repeatability"-values for each axis of all five machines together. These arithmetic mean values "unidirectional positioning repeatability" (UPR) become the stated value of each axis for the model (=)( $UPR_x, UPR_y, \dots$ );*
  - 5.d. *Since the Category 2 list refers to each linear axis there will be as many 'stated "unidirectional positioning repeatability"' values as there are linear axes;*
  - 5.e. *If any axis of a machine model not controlled by 2B001.a. to 2B001.c. has a 'stated "unidirectional positioning repeatability"' equal to or less than the specified "unidirectional positioning repeatability" of each machine tool model plus 0.7  $\mu\text{m}$ , the builder should be required to reaffirm the accuracy level once every eighteen months.*
6. *For the purpose of 2B, measurement uncertainty for the "unidirectional positioning repeatability" of machine tools, as defined in the International Standard ISO 230-2:2014, shall not be considered.*
7. *For the purpose of 2B, the measurement of axes shall be made according to test procedures in 5.3.2. of ISO 230-2:2014. Tests for axes longer than 2 meters shall be made over 2 m segments. Axes longer than 4m require multiple tests (e.g., two tests for axes longer than 4 m and up to 8 m, three tests for axes longer than 8 m and up to 12 m), each over 2 m segments and distributed in equal intervals over the axis length. Test segments are equally spaced along the full axis length, with any excess length equally divided at the beginning, in between, and at the end of the test segments. The smallest "unidirectional positioning repeatability"-value of all test segments is to be reported.*

2B991 Numerical control units for machine tools and “numerically controlled” machine tools, n.e.s. (see List of Items Controlled).

- a. “Numerical control” units for machine tools:
  - a.1. Having four interpolating axes that can be coordinated simultaneously for “contouring control”; *or*
  - a.2. Having two or more axes that can be coordinated simultaneously for “contouring control” and a minimum programmable increment better (less) than 0.001 mm;
  - a.3. “Numerical control” units for machine tools having two, three or four interpolating axes that can be coordinated simultaneously for “contouring control”, and capable of receiving directly (on-line) and processing computer-aided-design (CAD) data for internal preparation of machine instructions; *or*
- b. “Motion control boards” “specially designed” for machine tools and having any of the following characteristics:
  - b.1. Interpolation in more than four axes;
  - b.2. Capable of “real-time processing” of data to modify tool path, feed rate and spindle data, during the machining operation, by any of the following:
    - b.2.a. Automatic calculation and modification of part program data for machining in two or more axes by means of measuring cycles and access to source data; *or*
    - b.2.b. “Adaptive control” with more than one physical variable measured and processed by means of a computing model (strategy) to change one or more machining instructions to optimize the process.

- b.3. Capable of receiving and processing CAD data for internal preparation of machine instructions; *or*
- c. “Numerically controlled” machine tools that, according to the manufacturer's technical specifications, can be equipped with electronic devices for simultaneous “contouring control” in two or more axes and that have both of the following characteristics:
  - c.1. Two or more axes that can be coordinated simultaneously for contouring control; *and*
  - c.2. Positioning accuracies according to ISO 230/2 (2006), with all compensations available:
    - c.2.a. Better than 15  $\mu\text{m}$  along any linear axis (overall positioning) for grinding machines;
    - c.2.b. Better than 15  $\mu\text{m}$  along any linear axis (overall positioning) for milling machines; *or*
    - c.2.c. Better than 15  $\mu\text{m}$  along any linear axis (overall positioning) for turning machines; *or*
- d. Machine tools, as follows, for removing or cutting metals, ceramics or composites, that, according to the manufacturer's technical specifications, can be equipped with electronic devices for simultaneous “contouring control” in two or more axes:
  - d.1 Machine tools for turning, grinding, milling or any combination thereof, having two or more axes that can be coordinated simultaneously for “contouring control” and having any of the following characteristics:
    - d.1.a. One or more contouring “tilting spindles”;
    - Note: 2B991.d.1.a. applies to machine tools for grinding or milling only.*
    - d.1.b. “Camming” (axial displacement) in one revolution of the spindle less (better) than 0.0006 mm total indicator reading (TIR);
    - Note: 2B991.d.1.b. applies to machine tools for turning only.*
    - d.1.c. “Run out” (out-of-true running) in one revolution of the spindle less (better) than 0.0006 mm total indicator reading (TIR);
    - d.1.d. The “positioning accuracies”, with all compensations available, are less (better) than: 0.001° on any rotary axis;
  - d.2. Electrical discharge machines (EDM) of the wire feed type that have five or more axes that can be coordinated simultaneously for “contouring control”.

2B992 Non-"numerically controlled" machine tools for generating optical quality surfaces, (see List of Items Controlled) and “specially designed” “parts” and “components” therefor.

- a. Turning machines using a single point cutting tool and having all of the following characteristics:
  - a.1. Slide positioning accuracy less (better) than 0.0005 mm per 300 mm of travel;
  - a.2. Bidirectional slide positioning repeatability less (better) than 0.00025 mm per 300 mm of travel;
  - a.3. Spindle “run out” and “camming” less (better) than 0.0004 mm total indicator reading (TIR);
  - a.4. Angular deviation of the slide movement (yaw, pitch and roll) less (better) than 2 seconds of arc, TIR, over full travel; *and*
  - a.5. Slide perpendicularity less (better) than 0.001 mm per 300 mm of travel;

*Technical Note: The bidirectional slide positioning repeatability (R) of an axis is the maximum value of the repeatability of positioning at any position along or around the axis determined using the procedure and under the conditions specified in part 2.11 of ISO 230/2: 1988.*

b. Fly cutting machines having all of the following characteristics:

- a.1. Spindle “run out” and “camming” less (better) than 0.0004 mm TIR; and
- a.2. Angular deviation of slide movement (yaw, pitch and roll) less (better) than 2 seconds of arc, TIR, over full travel.

2B993 Gearmaking and/or finishing machinery not controlled by 2B003 capable of producing gears to a quality level of better than AGMA 11.

2B996 Dimensional inspection or measuring systems or equipment not controlled by 2B006 or 2B206, as follows (see List of Items Controlled).

a. Manual dimensional inspection machines, having both of the following characteristics:

- a.1. Two or more axes; *and*
- a.2. A measurement uncertainty equal to or less (better) than  $(3 + L/300)$  micrometer in any axes (L measured length in mm).

2B997 “Robots” not controlled by 2B007 or 2B207 that are capable of employing feedback information in real-time processing from one or more sensors to generate or modify “programs” or to generate or modify numerical program data.

2B998 Assemblies, circuit boards or inserts “specially designed” for machine tools controlled by 2B991, or for equipment controlled by 2B993, 2B996 or 2B997.

a. Spindle assemblies, consisting of spindles and bearings as a minimal assembly, with radial (“run out”) or axial (“camming”) axis motion in one revolution of the spindle less (better) than 0.0006 mm total indicator reading (TIR);

b. Single point diamond cutting tool inserts, having all of the following characteristics:

- b.1. Flawless and chip-free cutting edge when magnified 400 times in any direction;
- b.2. Cutting radius from 0.1 to 5 mm inclusive; *and*
- b.3. Cutting radius out-of-roundness less (better) than 0.002 mm TIR.

c. “Specially designed” printed circuit boards with mounted “parts” or “components” capable of upgrading, according to the manufacturer's specifications, “numerical control” units, machine tools or feed-back devices to or above the levels specified in ECCNs 2B991, 2B993, 2B996, 2B997, or 2B998.

2B999 Specific processing equipment, n.e.s., as follows (see List of Items Controlled).

a. Isostatic presses, n.e.s.;

b. Bellows manufacturing equipment, including hydraulic forming equipment and bellows forming dies;

c. Laser welding machines;

d. MIG welders;



- e. E-beam welders;
- f. Monel equipment, including valves, piping, tanks and vessels;
- g. 304 and 316 stainless steel valves, piping, tanks and vessels;

*Note: Fittings are considered part of "piping" for purposes of 2B999.g.*

- h. Mining and drilling equipment, as follows:
  - h.1. Large boring equipment capable of drilling holes greater than two feet in diameter;
  - h.2. Large earth-moving equipment used in the mining industry;
- i. Electroplating equipment designed for coating parts with nickel or aluminum;
- j. Pumps designed for industrial service and for use with an electrical motor of 5 HP or greater;
- k. Vacuum valves, piping, flanges, gaskets and related equipment "specially designed" for use in high-vacuum service, n.e.s.;
- l. Spin forming and flow forming machines, n.e.s.;
- m. Centrifugal multiplane balancing machines, n.e.s.;
- n. Austenitic stainless steel plate, valves, piping, tanks and vessels.

#### C. "MATERIALS" [RESERVED]

#### D. "SOFTWARE"

- 2D983 "Software" "specially designed" or modified for the "development", "production" or "use" of equipment controlled by 2A983.
- 2D984 "Software" "required" for the "development", "production" or "use" of concealed object detection equipment controlled by 2A984.
- 2D991 "Software" "specially designed" for the "development", "production", or "use" of equipment controlled by 2B991, 2B993, or 2B996, 2B997, and 2B998.
- 2D992 Specific "software", as follows (see List of Items Controlled).
  - a. "Software" to provide "adaptive control" and having both of the following characteristics:
    - a.1. For "flexible manufacturing units" (FMUs) which consist at least of equipment described in b.1 and b.2 of the definition of "flexible manufacturing unit" contained in part 772 of the EAR; *and*
    - a.2. Capable of generating or modifying, in "real-time processing", programs or data by using the signals obtained simultaneously by means of at least two detection techniques, such as:
      - a.2.a. Machine vision (optical ranging);
      - a.2.b. Infrared imaging;
      - a.2.c. Acoustical imaging (acoustical ranging);
      - a.2.d. Tactile measurement;
      - a.2.e. Inertial positioning;
      - a.2.f. Force measurement; *and*
      - a.2.g. Torque measurement.

*Note: 2D992.a does not control “software” which only provides rescheduling of functionally identical equipment within “flexible manufacturing units” using pre-stored part programs and a pre-stored strategy for the distribution of the part programs.*

b. [RESERVED].

2D993 “Software” “specially designed” or modified for the “development,” “production,” or “use” of items controlled by 2A992 or 2A993.

2D994 “Software” “specially designed” for the “development” or “production” of portable electric generators controlled by 2A994.

#### E. “TECHNOLOGY”

2E984 “Technology” “required” for the “development,” “production” or “use” of equipment controlled by 2A984 or “required” for the “development” of “software” controlled by 2D984.

2E991 “Technology” for the “use” of equipment controlled by 2B991, 2B993, 2B996, or 2B997.

2E993 “Technology” according to the General Technology Note for the “use” of equipment controlled by 2A992 or 2A993.

2E994 “Technology” for the “use” of portable electric generators controlled by 2A994.

### **Category 3 - Electronics**

3A991 Electronic devices and components.

- a. “Microprocessor microcircuits”, “microcomputer microcircuits”, and microcontroller microcircuits having any of the following:
  1. A performance speed of 5 GFLOPS or more and an arithmetic logic unit with an access width of 32 bit or more;
  2. A clock frequency rate exceeding 25 MHz; or
  3. More than one data or instruction bus or serial communication port that provides a direct external interconnection between parallel “microprocessormicrocircuits” with a transfer rate of 2,5 Mbyte/s;
- b. Storage integrated circuits, as follows:
  1. Electrically erasable programmable read-only memories (EEPROMs) with a storage capacity:
    - a. Exceeding 16 Mbits per package for flash memory types; or
    - b. Exceeding either of the following limits for all other EEPROM types:
      1. Exceeding 1 Mbit per package; or
      2. Exceeding 256 kbit per package and a maximum access time of less than 80 ns;
  2. Static random access memories (SRAMs) with a storage capacity:
    - a. Exceeding 1 Mbit per package; or
    - b. Exceeding 256 kbit per package and a maximum access time of less than 25 ns;
- c. Analog-to-digital converters having any of the following:
  1. A resolution of 8 bit or more, but less than 12 bit, with an output rate greater than 200 Mega Samples Per Second (MSPS);
  2. A resolution of 12 bit with an output rate greater than  $10^5$  Mega Samples per Second (MSPS);
  3. A resolution of more than 12 bit but equal to or less than 14 bit with an outputrate greater than 10 Mega Samples per Second (MSPS); or

4. A resolution of more than 14 bit with an output rate greater than 2,5 Mega Samples Per Second (MSPS);
- d. Field programmable logic devices having a maximum number of single-ended digital input/outputs between 200 and 700;
- e. Fast Fourier Transform (FFT) processors having a rated execution time for a 1 024 point complex FFT of less than 1 ms;
- f. Custom integrated circuits for which the function is unknown, or the control status of the equipment in which the integrated circuits will be used is unknown to the manufacturer, having any of the following:
  1. More than 144 terminals; or
  2. A typical “basic propagation delay time” of less than 0.4 ns;
- g. Traveling-wave “vacuum electronic devices”, pulsed or continuous wave, as follows:
  1. Coupled cavity devices, or derivatives thereof;
  2. Devices based on helix, folded waveguide, or serpentine waveguide circuits, or derivatives thereof, having any of the following:
    - a. An “instantaneous bandwidth” of half an octave or more and average power (expressed in kW) times frequency (expressed in GHz) of more than 0,2; or
    - b. An “instantaneous bandwidth” of less than half an octave; and average power (expressed in kW) times frequency (expressed in GHz) of more than 0,4;
- h. Flexible waveguides designed for use at frequencies exceeding 40 GHz;
- i. Surface acoustic wave and surface skimming (shallow bulk) acoustic wave devices, having either of the following:
  1. A carrier frequency exceeding 1 GHz; or
  2. A carrier frequency of 1 GHz or less; and
    - a. A “frequency side-lobe rejection” exceeding 55 dB;

- b. A product of the maximum delay time and bandwidth (time in microseconds and bandwidth in MHz) of more than 100; or
- c. A dispersive delay of more than 10 microseconds;

Technical Note: For the purpose of 3A991.i 'Frequency side-lobe rejection' is the maximum rejection value specified in data sheet.

- j. "Cells" as follows:
  - 1. "Primary cells" having an "energy density" of 550 Wh/kg or less at 293 K (20°C);
  - 2. "Secondary cells" having an "energy density" of 350 Wh/kg or less at 293 K (20°C);

Note: 3A991.j does not control batteries, including single cell batteries.

Technical Notes:

- 1. For the purpose of 3A991.j energy density (Wh/kg) is calculated from the nominal voltage multiplied by the nominal capacity in ampere-hours (Ah) divided by the mass in kilograms. If the nominal capacity is not stated, energy density is calculated from the nominal voltage squared then multiplied by the discharge duration in hours divided by the discharge load in Ohms and the mass in kilograms.
  - 2. For the purpose of 3A991.j, a "cell" is defined as an electrochemical device, which has positive and negative electrodes, and electrolyte, and is a source of electrical energy. It is the basic building block of a battery.
  - 3. For the purpose of 3A991.j.1, a "primary cell" is a "cell" that is not designed to be charged by any other source.
  - 4. For the purpose of 3A991.j.2, a "secondary cell" is a "cell" that is designed to be charged by an external electrical source.
- k. "Superconductive" electromagnets or solenoids specially designed to be fully charged or discharged in less than one minute, having all of the following:

Note: 3A991.k does not control "superconductive" electromagnets or solenoids designed for Magnetic Resonance Imaging (MRI) medical equipment.

- 1. Maximum energy delivered during the discharge divided by the duration of the discharge of more than 500 kJ per minute;
  - 2. Inner diameter of the current carrying windings of more than 250 mm; and
  - 3. Rated for a magnetic induction of more than 8T or "overall current density" in the winding of more than 300 A/mm<sup>2</sup>;
- l. Circuits or systems for electromagnetic energy storage, containing components manufactured from "superconductive" materials specially designed for operation at temperatures below the "critical temperature" of at least one of their "superconductive" constituents, having all of the following:
    - 1. Resonant operating frequencies exceeding 1 MHz;
    - 2. A stored energy density of 1 MJ/m<sup>3</sup> or more; and

- 3. A discharge time of less than 1 ms;
- m. Hydrogen/hydrogen-isotope thyratrons of ceramic-metal construction and rate for a peak current of 500 A or more;
- n. Not used;
- o. Solar cells, cell-interconnect-coverglass (CIC) assemblies, solar panels, and solar arrays, which are “space qualified” and not controlled by 3A001.e.4.

3A992 General purpose "electronic assemblies", modules and equipment.

- a. Electronic test equipment, other than those specified in the CML or in Regulation (EU) 2021/821;
- b. Digital instrumentation magnetic tape data recorders having any of the following characteristics;
  - 1. A maximum digital interface transfer rate exceeding 60 Mbit/s and employing helical scan techniques;
  - 2. A maximum digital interface transfer rate exceeding 120 Mbit/s and employing fixed head techniques; or
  - 3. “Space qualified”;
- c. Equipment, with a maximum digital interface transfer rate exceeding 60 Mbit/s, designed to convert digital video magnetic tape recorders for use as digital instrumentation data recorders;
- d. Non-modular analog oscilloscopes having a bandwidth of 1 GHz or greater;
- e. Modular analog oscilloscope systems having either of the following characteristics:
  - 1. A mainframe with a bandwidth of 1 GHz or greater; or
  - 2. Plug-in modules with an individual bandwidth of 4 GHz or greater;
- f. Analog sampling oscilloscopes for the analysis of recurring phenomena with an effective bandwidth greater than 4 GHz;
- g. Digital oscilloscopes and transient recorders, using analog-to-digital conversion techniques, capable of storing transients by sequentially sampling single-shot inputs at successive intervals of less than 1 ns (greater than 1 Giga Samples per Second (GSPS)), digitizing to 8 bits or greater resolution and storing 256 or more samples.

Note: 3A992 controls the following specially designed components for analog oscilloscopes:

1. Plug-in units;
2. External amplifiers;
3. Pre-amplifiers;
4. Sampling devices;
5. Cathode ray tubes.

3A999 Specific processing equipment, other than those specified in the CML or in Regulation (EU) 2021/821, as follows:

- a. Frequency changers capable of operating in the frequency range from 300 up to 600 Hz, other than those specified in the CML or in Regulation (EU) 2021/821;
- b. Mass spectrometers, other than those specified in the CML or in Regulation (EU) 2021/821;
- c. All flash x-ray machines, or components of pulsed power systems designed thereof, including Marx generators, high power pulse shaping networks, high voltage capacitors, and triggers;
- d. Pulse amplifiers, other than those specified in the CML or in Regulation (EU) 2021/821;
- e. Electronic equipment for time delay generation or time interval measurement, as follows:
  1. Digital time delay generators with a resolution of 50 nanoseconds or less over time intervals of 1 microsecond or greater; or
  2. Multi-channel (three or more) or modular time interval meter and chronometry equipment with resolution of 50 nanoseconds or less over time intervals of 1 microsecond or greater;
- f. Chromatography and spectrometry analytical instruments.

3B991 Equipment for the manufacture of electronic components or materials, as follows and specially designed components and accessories therefor.

- a. Equipment specially designed for the manufacture of electron tubes, optical elements and specially designed components therefor controlled by 3A001 or 3A991;
- b. Equipment specially designed for the manufacture of semiconductor devices, integrated circuits and “electronic assemblies”, as follows, and systems incorporating or having the characteristics of such equipment:

Note: 3B991.b. also controls equipment used or modified for use in the manufacture of other devices, such as imaging devices, electro-optical devices, acoustic-wave devices.

1. Equipment for the processing of materials for the manufacture of devices and components as specified in the heading of 3B991.b, as follows:

Note: 3B991 does not control quartz furnace tubes, furnace liners, paddles, boats (except specially designed caged boats), bubblers, cassettes or crucibles specially designed for the processing equipment controlled by 3B991.b.1.

- a. Equipment for producing polycrystalline silicon and materials controlled by 3C001;
- b. Equipment specially designed for purifying or processing III/V and II/VI semiconductor materials controlled by 3C001, 3C002, 3C003, 3C004, or 3C005 except crystal pullers, for which see 3B991.b.1.c below;
- c. Crystal pullers and furnaces, as follows:

Note: 3B991.b.1.c does not control diffusion and oxidation furnaces.

1. Annealing or recrystallizing equipment other than constant temperature furnaces employing high rates of energy transfer capable of processing wafers at a rate exceeding 0,005 m<sup>2</sup> per minute;
2. "Stored program controlled" crystal pullers having any of the following characteristics:
  - a. Rechargeable without replacing the crucible container;
  - b. Capable of operation at pressures above 2.5 x 10<sup>5</sup> Pa; or
  - c. Capable of pulling crystals of a diameter exceeding 100 mm;
- d. "Stored program controlled" equipment for epitaxial growth having any of the following characteristics:
  1. Capable of producing silicon layer with a thickness uniform to less than ± 2.5 % across a distance of 200 mm or more;
  2. Capable of producing a layer of any material other than silicon with a thickness uniformity across the wafer of equal to or better than ± 3.5 %; or
  3. Rotation of individual wafers during processing;
- e. Molecular beam epitaxial growth equipment;
- f. Magnetically enhanced "sputtering" equipment with specially designed integral load locks capable of transferring wafers in an isolated vacuum environment;
- g. Equipment specially designed for ion implantation, ion-enhanced or photo-enhanced diffusion, having any of the following characteristics:
  1. Patterning capability;



2. Beam energy (accelerating voltage) exceeding 200 keV;
  3. Optimised to operate at a beam energy (accelerating voltage) of less than 10 keV; or
  4. Capable of high energy oxygen implant into a heated “substrate”;
- h. “Stored program controlled” equipment for the selective removal (etching) by means of anisotropic dry methods (e.g., plasma), as follows:
1. “Batch types” having either of the following:
    - a. End-point detection, other than optical emission spectroscopy types; or
    - b. Reactor operational (etching) pressure of 26.66 Pa or less;
  2. “Single wafer types” having any of the following:
    - a. End-point detection, other than optical emission spectroscopy types;
    - b. Reactor operational (etching) pressure of 26.66 Pa or less; or
    - c. Cassette-to-cassette and load locks wafer handling;

Notes:

1. “Batch types” refers to machines not specially designed for production processing of single wafers. Such machines can process two or more wafers simultaneously with common process parameters, e.g., RF power, temperature, etch gas species, flow rates.
  2. “Single wafer types” refers to machines specially designed for production processing of single wafers. These machines may use automatic wafer handling techniques to load a single wafer into the equipment for processing. The definition includes equipment that can load and process several wafers but where the etching parameters, e.g., RF power or end point, can be independently determined for each individual wafer.
- i. “Chemical vapor deposition” (CVD) equipment, e.g., plasma-enhanced CVD (PECVD) or photo-enhanced CVD, for semiconductor device manufacturing, having either of the following capabilities, for deposition of oxides, nitrides, metals or polysilicon:
1. “Chemical vapor deposition” equipment operating below 105 Pa; or
  2. PECVD equipment operating either below 60 Pa or having automatic cassette-to-cassette and load lock wafer handling;
- Note: 3B991.b.1.i does not control low pressure “chemical

vapor deposition” (LPCVD) systems or reactive “sputtering” equipment.

- j. Electron beam systems specially designed or modified for mask making or semiconductor device processing having any of the following characteristics:

1. Electrostatic beam deflection;
2. Shaped, non-Gaussian beam profile;
3. Digital-to-analog conversion rate exceeding 3 MHz;
4. Digital-to-analog conversion accuracy exceeding 12 bit; or
5. Target-to-beam position feedback control precision of 1 micrometer or finer;

Note: 3B991.b.1.j does not control electron beam deposition systems or general purpose scanning electron microscopes.

- k. Surface finishing equipment for the processing of semiconductor wafers as follows:

1. Specially designed equipment for backside processing of wafers thinner than 100 micrometer and the subsequent separation thereof; or
2. Specially designed equipment for achieving a surface roughness of the active surface of a processed wafer with a two-sigma value of 2 micrometer or less, total indicator reading (TIR);

Note: 3B991.b.1.k does not control single-side lapping and polishing equipment for wafer surface finishing.

1. Interconnection equipment which includes common single or multiple vacuum chambers specially designed to permit the integration of any equipment controlled by 3B991 into a complete system;
- m. “Stored program controlled” equipment using “lasers” for the repair or trimming of “monolithic integrated circuits” with either of the following characteristics:
1. Positioning accuracy less than  $\pm 1$  micrometer; or
  2. Spot size (kerf width) less than 3 micrometer.

Technical Note: For the purpose of 3B991.b.1, 'sputtering' is an overlay coating process wherein positively charged ions are accelerated by an electric field towards the surface of a target (coating material). The kinetic energy of the impacting ions is sufficient to cause target surface atoms to be released and deposited on the substrate. (Note: Triode, magnetron or radio frequency sputtering to increase adhesion of coating and rate of deposition are ordinary modifications of the process.).

2. Masks, mask substrates, mask-making equipment and image transfer equipment for the manufacture of devices and components as specified in the heading of 3B991, as follows:

Note: The term masks refers to those used in electron beam lithography, X-ray lithography, and ultraviolet lithography, as well as the usual ultraviolet and visible photo-lithography.

- a. Finished masks, reticles and designs therefor, except:
  1. Finished masks or reticles for the production of integrated circuits not controlled by 3A001; or
  2. Masks or reticles, having both of the following characteristics:
    - a. Their design is based on geometries of 2.5 micrometer or more; and
    - b. The design does not include special features to alter the intended use by means of production equipment or “software”;
- b. Mask substrates as follows:
  1. Hard surface (e.g., chromium, silicon, molybdenum) coated “substrates” (e.g., glass, quartz, sapphire) for the preparation of masks having dimensions exceeding 125 mm x 125 mm; or
  2. Substrates specially designed for X-ray masks;
- c. Equipment, other than general purpose computers, specially designed for computer aided design (CAD) of semiconductor devices or integrated circuits;
- d. Equipment or machines, as follows, for mask or reticle fabrication:
  1. Photo-optical step and repeat cameras capable of producing arrays larger than 100 mm x 100 mm, or capable of producing a single exposure larger than 6 mm x 6 mm in the image (i.e., focal) plane, or capable of producing line widths of less than 2.5 micrometer in the photoresist on the “substrate”;
  2. Mask or reticle fabrication equipment using ion or “laser” beam lithography capable of producing line widths of less than 2.5 micrometer; or
  3. Equipment or holders for altering masks or reticles or adding pellicles to remove defects;

Note: 3B991.b.2.d.1 and b.2.d.2 do not control mask fabrication equipment using photo-optical methods which was either commercially available before the 1<sup>st</sup> January 1980, or has a performance no better than such equipment.

- e. “Stored program controlled” equipment for the inspection of masks, reticles or pellicles with:
  1. A resolution of 0.25 micrometer or finer; and
  2. A precision of 0.75 micrometer or finer over a distance in one or two coordinates of 63.5 mm or more;

Note: 3B991.b.2.e does not control general purpose scanning electron microscopes except when specially designed and instrumented for automatic pattern inspection.

- f. Align and expose equipment for wafer production using photo-optical or X-ray methods, e.g., lithography equipment, including both projection image transfer equipment and step and repeat (direct step on wafer) or step and scan (scanner) equipment, capable of performing any of the following functions:  
 Note: 3B991.b.2.f does not control photo-optical contact and proximity mask align and expose equipment or contact imagetransfer equipment.
    - 1. Production of a pattern size of less than 2.5 micrometer;
    - 2. Alignment with a precision finer than  $\pm 0.25$  micrometer (3 sigma);
    - 3. Machine-to-machine overlay no better than  $\pm 0.3$  micrometer; or
    - 4. A light source wavelength shorter than 400 nm;
  - g. Electron beam, ion beam or X-ray equipment for projection imagetransfer capable of producing patterns less than 2.5 micrometer;  
 Note: For focused, deflected-beam systems (direct write systems), see 3B991.b.1.j.
  - h. Equipment using "lasers" for direct write on wafers capable of producing patterns less than 2.5 micrometer.
3. Equipment for the assembly of integrated circuits, as follows:
- a. "Stored program controlled" die bonders having all of the following characteristics:
    - 1. Specially designed for "hybrid integrated circuits";
    - 2. X-Y stage positioning travel exceeding 37.5 x 37.5 mm; and
    - 3. Placement accuracy in the X-Y plane of finer than  $\pm 10$  micrometer;
  - b. "Stored program controlled" equipment for producing multiple bonds in a single operation (e.g., beam lead bonders, chip carrier bonders, tape bonders);
  - c. Semi-automatic or automatic hot cap sealers, in which the cap is heated locally to a higher temperature than the body of the package, specially designed for ceramic microcircuit packages controlled by 3A001 and that have a throughput equal to or more than one package per minute.
- Note: 3B991.b.3 does not control general purpose resistance type spotwelders.
4. Filters for clean rooms capable of providing an air environment of 10 or less particles of 0.3 micrometer or smaller per 0.02832 m<sup>3</sup> and filter materials therefor.

Technical Note: For the purpose of 3B991, 'stored program controlled' is a control using instructions stored in an electronic storage that a processor can execute in order to direct the performance of predetermined functions. Equipment may be 'stored program controlled' whether the electronic storage is internal or external to the equipment.

3B992 Equipment for the inspection or testing of electronic components and materials, and specially designed components and accessories therefor.

- a. Equipment specially designed for the inspection or testing of electron tubes, optical elements and specially designed components therefor controlled by 3A001 or 3A991;
- b. Equipment specially designed for the inspection or testing of semiconductor devices, integrated circuits and “electronic assemblies”, as follows, and systems incorporating or having the characteristics of such equipment:

Note: 3B992.b also controls equipment used or modified for use in the inspection or testing of other devices, such as imaging devices, electro-optical devices, acoustic-wave devices.

- 1. “Stored program controlled” inspection equipment for the automatic detection of defects, errors or contaminants of 0,6 micrometer or less in or on processed wafers, substrates, other than printed circuit boards or chips, using optical image acquisition techniques for pattern comparison;

Note: 3B992.b.1 does not control general purpose scanning electron microscopes, except when specially designed and instrumented for automatic pattern inspection.

- 2. Specially designed “stored program controlled” measuring and analysis equipment, as follows:
  - a. Specially designed for the measurement of oxygen or carbon content in semiconductor materials;
  - b. Equipment for line width measurement with a resolution of 1 micrometer or finer;
  - c. Specially designed flatness measurement instruments capable of measuring deviations from flatness of 10 micrometer or less with a resolution of 1 micrometer or finer.
- 3. “Stored program controlled” wafer probing equipment having any of the following characteristics:
  - a. Positioning accuracy finer than 3,5 micrometer;
  - b. Capable of testing devices having more than 68 terminals; or
  - c. Capable of testing at a frequency exceeding 1 GHz;
- 4. Test equipment as follows:
  - a. “Stored program controlled” equipment specially designed for testing

discrete semiconductor devices and unencapsulated dice, capable of testing at frequencies exceeding 18 GHz;

Technical Note: Discrete semiconductor devices include photocells and solar cells.

b. “Stored program controlled” equipment specially designed for testing integrated circuits and “electronic assemblies” thereof, capable of functional testing:

1. At a “pattern rate” exceeding 20 MHz; or
2. At a “pattern rate” exceeding 10 MHz but not exceeding 20 MHz and capable of testing packages of more than 68 terminals.

Notes: 3B992.b.4.b does not control test equipment specially designed for testing:

1. Memories;
2. “Assemblies” or a class of “electronic assemblies” for home and entertainment applications; and
3. Electronic components, “electronic assemblies” and integrated circuits not controlled by 3A001 or 3A991 provided such test equipment does not incorporate computing facilities with “user accessible programmability”.

Technical Note: For purposes of 3B992.b.4.b, “pattern rate” is defined as the maximum frequency of digital operation of a tester. It is therefore equivalent to the highest data rate that a tester can provide in non-multiplexed mode. It is also referred to as test speed, maximum digital frequency or maximum digital speed.

c. Equipment specially designed for determining the performance of focal-plane arrays at wavelengths of more than 1,200 nm, using “stored program controlled” measurements or computer aided evaluation and having any of the following characteristics:

1. Using scanning light spot diameters of less than 0.12 mm;
2. Designed for measuring photosensitive performance parameters and for evaluating frequency response, modulation transfer function, uniformity of responsivity or noise; or
3. Designed for evaluating arrays capable of creating images with more than 32 x 32 line elements;

5. Electron beam test systems designed for operation at 3 keV or below, or “laser” beam systems, for non-contactive probing of powered-up semiconductor devices having any of the following:

- a. Stroboscopic capability with either beam blanking or detector strobing;
- b. An electron spectrometer for voltage measurements with a resolution of less than 0.5 V; or
- c. Electrical tests fixtures for performance analysis of integrated circuits;

Note: 3B992.b.5 does not control scanning electron microscopes, except when specially designed and instrumented for non-contactive probing of a powered-up semiconductor device.

- 6. “Stored program controlled” multifunctional focused ion beam systems specially designed for manufacturing, repairing, physical layout analysis and testing of masks or semiconductor devices and having either of the following characteristics:
  - a. Target-to-beam position feedback control precision of 1 micrometer or finer; or
  - b. Digital-to-analog conversion accuracy exceeding 12 bit;
- 7. Particle measuring systems employing “lasers” designed for measuring particle size and concentration in air having both of the following characteristics:
  - a. Capable of measuring particle sizes of 0,2 micrometer or less at a flow rate of 0,02832 m<sup>3</sup> per minute or more; and
  - b. Capable of characterizing Class 10 clean air or better.

Technical Note: For the purpose of 3B992, “stored program controlled” is a control using instructions stored in an electronic storage that a processor can execute in order to direct the performance of predetermined functions. Equipment may be “stored program controlled” whether the electronic storage is internal or external to the equipment.

3C991 Positive resists designed for semiconductor lithography specially adjusted (optimised) for use at wavelengths between 370 and 193 nm.

3D991 “Software” specially designed for the “development”, “production”, or “use” of electronic devices or components controlled by 3A991, general purpose electronic equipment controlled by 3A992, or manufacturing and test equipment controlled by 3B991 and 3B992; or “software” specially designed for the “use” of equipment controlled by 3B001.g and 3B001.h.

3E991 “Technology” for the “development”, “production” or “use” of electronic devices or components controlled by 3A991, general purpose electronic equipment controlled by 3A992, or manufacturing and test equipment controlled by 3B991 or 3B992, or materials controlled by 3C991.

## Category4 – Computers

Note: Category 4 does not control goods for the personal use of the natural persons.

4A994 Computers, “electronic assemblies” and related equipment, not controlled by 4A001 or 4A003, and specially designed components therefor.

Note: The control status of the “digital computers” and related equipment described in 4A994 is determined by the control status of other equipment or systems provided:

- a. The “digital computers” or related equipment are essential for the operation of the other equipment or systems;
- b. The “digital computers” or related equipment are not a “principal element” of the other equipment or systems; and

N.B.1: The control status of “signal processing” or “image enhancement” equipment specially designed for other equipment with functions limited to those required for the other equipment is determined by the control status of the other equipment even if it exceeds the “principal element” criterion.

N.B.2: For the control status of “digital computers” or related equipment for telecommunications equipment, see Category 5.Part 1 (Telecommunications).

- c. The “technology” for the “digital computers” and related equipment is determined by 4E.
    - a. Electronic computers and related equipment, and “electronic assemblies” and specially designed components therefor, rated for operation at an ambient temperature above 343 K (70°C);
    - b. “Digital computers”, including equipment of “signal processing” or image enhancement”, having an “Adjusted Peak Performance” (“APP”) equal to or greater than 0.0128 Weighted TeraFLOPS (WT);
    - c. “Electronic assemblies” that are specially designed or modified to enhance performance by aggregation of processors, as follows:
      1. Designed to be capable of aggregation in configurations of 16 or more processors;
      2. Not used;
- Note 1: 4A994.c applies only to “electronic assemblies” and programmable interconnections with a “APP” not exceeding the limits in 4A994.b, when shipped as unintegrated “electronic assemblies”. It does not apply to “electronic assemblies” inherently limited by nature of their design for use as related equipment controlled by 4A994.k.
- Note 2: 4A994.c does not control any “electronic assembly” specially designed for a product or family of products whose maximum configuration does not exceed the limits of 4A994.b.
- d. Not used;



- e. Not used;
- f. Equipment for “signal processing” or “image enhancement” having an “Adjusted Peak Performance” (“APP”) equal to or greater than 0.0128 Weighted TeraFLOPS WT;
- g. Not used;
- h. Not used;
- i. Equipment containing “terminal interface equipment” exceeding the limits in 5A991;

Technical Note: For the purpose of 4A994.i, “terminal interface equipment” means equipment at which information enters or leaves the telecommunication system, e.g. telephone, data device, computer, etc.

- j. Equipment specially designed to provide external interconnection of “digital computers” or associated equipment that allows communications at data rates exceeding 80 Mbyte/s.

Note: 4A994.j does not control internal interconnection equipment (e.g., backplanes, buses) passive interconnection equipment, “network access controllers” or “communication channel controllers”.

Technical Note: For the purpose of 4A994.j, “communication channel controllers” is the physical interface which controls the flow of synchronous or asynchronous digital information. It is an assembly that can be integrated into computer or telecommunications equipment to provide communications access.

- k. “Hybrid computers” and “electronic assemblies” and specially designed components therefor containing analog-to-digital converters having all of the following characteristics:
  1. 32 channels or more; and
  2. A resolution of 14 bit (plus sign bit) or more with a conversion rate of 200 000 Hz or more.

4D993 “Program” proof and validation “software”, “software” allowing the automatic generation of “source codes”, and operating system “software” that are specially designed for “real-time processing” equipment.

- a. “Program” proof and validation “software” using mathematical and analytical techniques and designed or modified for “programs” having more than 500 000 “source code” instructions;
- b. “Software” allowing the automatic generation of “source codes” from data acquired on line from external sensors described in the Regulation (EU) 2021/821; or

- c. Operating system “software” specially designed for “real-time processing” equipment that guarantees a “global interrupt latency time” of less than 20 microseconds.

Technical Note: For the purpose of 4D993, 'global interrupt latency time' is the time taken by the computer system to recognise an interrupt due to the event, service the interrupt and perform a context switch to an alternate memory-resident task waiting on the interrupt.

4D994 “Software” other than that controlled in 4D001 specially designed or modified for the “development”, “production” or “use” of equipment controlled by 4A101, 4A994.

4E992 “Technology” for the “development”, “production” or “use” of equipment controlled by 4A994, or “software” controlled by 4D993 or 4D994.

4E993 “Technology” for the “development” or “production” of equipment designed for 'multi-data-stream processing'.

Technical Note: For the purpose of 4E992, “multi-data-stream processing” is a microprogram or equipment architecture technique that permits simultaneous processing of two or more data sequences under the control of one or more instruction sequences by means such as:

1. Single Instruction Multiple Data (SIMD) architectures such as vector or array processors;
2. Multiple Single Instruction Multiple Data (MSIMD) architectures;
3. Multiple Instruction Multiple Data (MIMD) architectures, including those that are tightly coupled, closely coupled or loosely coupled; or
4. Structured arrays of processing elements, including systolic arrays.

## Category 5. Part 1 – Telecommunications

Note: Category 5.Part 1 does not control goods for the personal use of the natural persons.

5A991 Telecommunication equipment.

- a. Any type of telecommunications equipment, not controlled by 5A001.a, specially designed to operate outside the temperature range from 219 K (-54°C) to 397 K (124°C).
- b. Telecommunication transmission equipment and systems, and specially designed components and accessories therefor, having any of the following characteristics, functions or features:

Note: Telecommunication transmission equipment:

- a. Categorised as follows, or combinations thereof:
    1. Radio equipment (e.g., transmitters, receivers and transceivers);
    2. Line terminating equipment;
    3. Intermediate amplifier equipment;
    4. Repeater equipment;
    5. Regenerator equipment;
    6. Translation encoders (transcoders);
    7. Multiplex equipment (statistical multiplex included);
    8. Modulators/demodulators (modems);
    9. Transmultiplex equipment (see CCITT Rec. G701);
    10. "Stored program controlled" digital cross-connection equipment;
    11. "Gateways" and bridges;
    12. "Media access units"; and
  - b. Designed for use in single or multi-channel communication via any of the following:
    1. Wire (line);
    2. Coaxial cable;
    3. Optical fibre cable;
    4. Electromagnetic radiation; or
    5. Underwater acoustic wave propagation.
1. Employing digital techniques, including digital processing of analog signals, and designed to operate at a "digital transfer rate" at the highest multiplex level exceeding 45 Mbit/s or a "total digital transfer rate" exceeding 90 Mbit/s;

Note: 5A991.b.1 does not control equipment specially designed to be integrated and operated in any satellite system for civil use.
  2. Modems using the "bandwidth of one voice channel" with a "data signalling rate" exceeding 9,600 bits per second;
  3. Being "stored program controlled" digital cross connect equipment with "digital transfer rate" exceeding 8.5 Mbit/s per port.
  4. Being equipment containing any of the following:
    - a. "Network access controllers" and their related common medium having a "digital transfer rate" exceeding 33 Mbit/s; or

- b. “Communication channel controllers” with a digital output having a “data signalling rate” exceeding 64,000 bit/s per channel;

Note: If any uncontrolled equipment contains a “network access controller”, it cannot have any type of telecommunications interface, except those described in, but not controlled by 5A991.b.4.

- 5. Employing a “laser” and having any of the following characteristics:

- a. A transmission wavelength exceeding 1,000 nm; or
- b. Employing analog techniques and having a bandwidth exceeding 45 MHz;
- c. Employing coherent optical transmission or coherent optical detection techniques (also called optical heterodyne or homodyne techniques);
- d. Employing wavelength division multiplexing techniques; or
- e. Performing “optical amplification”;

- 6. Radio equipment operating at input or output frequencies exceeding:

- a. 31 GHz for satellite-earth station applications; or
- b. 26.5 GHz for other applications;

Note: 5A991.b.6 does not control equipment for civil use when conforming with an International Telecommunications Union (ITU) allocated band between 26.5 GHz and 31 GHz.

- 7. Being radio equipment employing any of the following:

- a. Quadrature-amplitude-modulation (QAM) techniques above level 4 if the “total digital transfer rate” exceeds 8.5 Mbit/s;
- b. QAM techniques above level 16 if the “total digital transfer rate” is equal to or less than 8.5 Mbit/s;
- c. Other digital modulation techniques and having a “spectral efficiency” exceeding 3 bit/s/Hz; or
- d. Operating in the 1.5 MHz to 87.5 MHz band and incorporating adaptive techniques providing more than 15 dB suppression of an interfering signal.

Notes:

- 1. 5A991.b.7 does not control equipment specially designed to be integrated and operated in any satellite system for civil use.
- 2. 5A991.b.7 does not control radio relay equipment for operation in an International Telecommunications Union (ITU) allocated band:

- a. Having any of the following:
  - 1. Not exceeding 960 MHz; or
  - 2. With a “total digital transfer rate” not exceeding 8.5 Mbit/s; and
- b. Having a “spectral efficiency” not exceeding 4 bit/s/Hz.
- c. “Stored program controlled” switching equipment and related signalling systems, having any of the following characteristics, functions or features, and specially designed components and accessories therefor:

Note: Statistical multiplexers with digital input and digital output which provide switching are treated as 'stored program controlled' switches.

- 1. “Data (message) switching” equipment or systems designed for “packet-mode operation”, electronic assemblies and components therefor, other than those specified in the CML or in Regulation (EU) 2021/821.
- 2. Not used;
- 3. Routing or switching of “datagram” packets;

Note: 5A991.c.3 does not control networks restricted to using only “network access controllers” or to “network access controllers” themselves.

- 4. Not used;
- 5. Multi-level priority and pre-emption for circuit switching;

Note: 5A991.c.5 does not control single-level call preemption.

- 6. Designed for automatic hand-off of cellular radio calls to other cellular switches or automatic connection to a centralised subscriber data base common to more than one switch;
- 7. Containing “stored program controlled” digital cross connect equipment with “digital transfer rate” exceeding 8.5 Mbit/s per port.
- 8. “Common channel signalling” operating in either non-associated or quasi-associated mode of operation;
- 9. “Dynamic adaptive routing”;
- 10. Being packet switches, circuit switches and routers with ports or lines exceeding any of the following:

- a. A “data signalling rate” of 64,000 bit/s per channel for a ‘communications channel controller’; or

Note: 5A991.c.10.a does not control multiplex composite links composed only of communication channels not individually

controlled by 5A991.b.1.

- b. A “digital transfer rate” of 33 Mbit/s for a “network access controller” and related common media;

Note: 5A991.c.10 does not control packet switches or routers with ports or lines not exceeding the limits in 5A991.c.10.

11. “Optical switching”;

12. Employing “Asynchronous Transfer Mode” (“ATM”) techniques.

d. Optical fibres and optical fibre cables of more than 50 m in length designed for single mode operation;

e. Centralised network control having all of the following characteristics:

- 1. Receives data from the nodes; and
- 2. Process these data in order to provide control of traffic not requiring operator decisions, and thereby performing “dynamic adaptive routing”;

Note 1: 5A991.e does not include cases of routing decisions taken on predefined information.

Note 2: 5A991.e does not preclude control of traffic as a function of predictable statistical traffic conditions.

f. Phased array antennas, operating above 10.5 GHz, containing active elements and distributed components, and designed to permit electronic control of beam shaping and pointing, except for landing systems with instruments meeting International Civil Aviation Organization (ICAO) standards (microwave landing systems (MLS)).

g. Mobile communications equipment other than those specified in the CML or in Regulation (EU) 2021/821, electronic assemblies and components therefor; or

h. Radio relay communications equipment designed for use at frequencies equal to or exceeding 19.7 GHz and components therefor, other than those specified in the CML or in Regulation (EU) 2021/821.

Technical Note: For the purpose of 5A991:

- 1) “Asynchronous transfer mode” (“ATM”) is a transfer mode in which the information is organised into cells; it is asynchronous in the sense that the recurrence of cells depends on the required or instantaneous bit rate.
- 2) “Bandwidth of one voice channel” is data communication equipment designed to operate in one voice channel of 3,100 Hz, as defined in CCITT Recommendation G.151.
- 3) “Communications channel controller” is the physical interface that controls the flow of synchronous or asynchronous digital information. It is an assembly that can be integrated into computer or telecommunications equipment to provide

communications access.

- 4) “Datagram” is a self-contained, independent entity of data carrying sufficient information to be routed from the source to the destination data terminal equipment without reliance on earlier exchanges between this source and destination data terminal equipment and the transporting network.
- 5) “Fast select” is a facility applicable to virtual calls that allows data terminal equipment to expand the possibility to transmit data in call set-up and clearing “packets” beyond the basic capabilities of a virtual call.
- 6) “Gateway” is the function, realised by any combination of equipment and “software”, to carry out the conversion of conventions for representing, processing or communicating information used on one system into the corresponding, but different conventions used in another system.
- 7) “Integrated Services Digital Network” (ISDN) is a unified end-to-end digital network, in which data originating from all types of communication (e.g., voice, text, data, still and moving pictures) are transmitted from one port (terminal) in the exchange (switch) over one access line to and from the subscriber.
- 8) “Packet” is a group of binary digits including data and call control signals that is switched as a composite whole. The data, call control signals, and possible error control information are arranged in a specified format.
- 9) “Common channel signalling” means the transmission of control information (signalling) via a separate channel than that used for the messages. The signalling channel usually controls multiple message channels.
- 10) “Data signalling rate” means the rate, as defined in ITU Recommendation 53-36, taking into account that, for non-binary modulation, baud and bit per second are not equal. Bits for coding, checking and synchronization functions are to be included.
- 11) “Dynamic adaptive routing” means Automatic rerouting of traffic based on sensing and analysis of current actual network conditions
- 12) “Media access unit” means equipment that contains one or more communication interfaces (“network access controller”, “communications channel controller”, modem or computer bus) to connect terminal equipment to a network.
- 13) “Spectral efficiency” is the “digital transfer rate” [bits/s] / 6 dB spectrum bandwidth inHz.
- 14) “Stored program controlled” is a control using instructions stored in an electronic storage that a processor can execute in order to direct the performance of predetermined functions. Note: Equipment may be “stored program controlled” whether the electronic storage is internal or external to the equipment.

5B991 Telecommunications test equipment, other than those specified in the CML or in Regulation (EU) 2021/821.

5C991 Preforms of glass or of any other material optimised for the manufacture of opticalfibres controlled by 5A991.

5D991 “Software” specially designed or modified for the “development”, “production” or “use” of equipment controlled by 5A991 and 5B991, and dynamic adaptive routing software as described as follows:

- a. “Software”, other than in machine-executable form, specially designed for “dynamic adaptive routing”.
- b. Not used;

5E991 “Technology” for the “development”, “production” or “use” of equipment controlled by 5A991 or 5B991, or “software” controlled by 5D991, and other “technologies” as follows:

- a. Specific “technologies” as follows:
  1. “Technology” for the processing and application of coatings to optical fibre specially designed to make it suitable for underwater use;
  2. “Technology” for the “development” of equipment employing “Synchronous Digital Hierarchy” (“SDH”) or “Synchronous Optical Network” (“SONET”) techniques.

Technical Note: For the purpose of 5E991:

- 1) “Synchronous digital hierarchy” (SDH) is a digital hierarchy providing a means to manage, multiplex, and access various forms of digital traffic using a synchronous transmission format on different types of media. The format is based on the Synchronous Transport Module (STM) that is defined by CCITT Recommendation G.703, G.707, G.708, G.709 and others yet to be published. The first level rate of “SDH” is 155.52 Mbits/s.
- 2) “Synchronous optical network” (SONET) is a network providing a means to manage, multiplex and access various forms of digital traffic using a synchronous transmission format on fibre optics. The format is the North America version of “SDH” and also uses the Synchronous Transport Module (STM). However, it uses the Synchronous Transport Signal (STS) as the basic transport module with a first level rate of 51.81 Mbits/s. The SONET standards are being integrated into those of “SDH”.



## Category 5. Part 2 - Information Security

Note: Category 5. Part 2 does not control goods for the personal use of the natural persons.

5A992 Equipment as follows:

- a. Not used;
- b. Not used;
- c. Goods classified as mass market encryption in accordance with Cryptography Note – Note 3 to Category 5. Part 2.

5D992 “Information Security” “software” as follows:

Note: This entry does not control “software” designed or modified to protect against malicious computer damage, e.g., viruses, where the use of “cryptography” is limited to authentication, digital signature and/or the decryption of data or files.

- a. Not used;
- b. Not used;
- c. “Software” classified as mass market encryption software in accordance with Cryptography Note – Note 3 to Category 5. Part 2.

5E992 “Information Security” “technology” according to the General Technology Note, as follows:

- a. Not used;
- b. “Technology”, other than specified in the CML or in Regulation (EU) 2021/821, for the “use” of mass market goods controlled by 5A992.c or mass market “software” controlled by 5D992.c.

## Category 6 – Sensors and Lasers

6A991 Marine or terrestrial acoustic equipment, capable of detecting or locating underwater objects or features or positioning surface vessels or underwater vehicles; and specially designed components, other than those specified in the CML or in Regulation(EU) 2021/821.

6A992 Optical Sensors as follows:

- a. Image intensifier tubes and specially designed components therefor, as follows:
  1. Image intensifier tubes having all the following:
    - a. A peak response in wavelength range exceeding 400 nm, but not exceeding 1,050 nm;
    - b. A microchannel plate for electron image amplification with a hole pitch (center-to-center spacing) of less than 25 micrometers; and
    - c. Having any of the following:
      1. An S-20, S-25 or multialkali photocathode; or
      2. A GaAs or GaInAs photocathode;
  2. Specially designed microchannel plates having both of the following characteristics:
    - a. 15,000 or more hollow tubes per plate; and
    - b. Hole pitch (center-to-center spacing) of less than 25 micrometers.
- b. Direct view imaging equipment operating in the visible or infrared spectrum, incorporating image intensifier tubes having the characteristics listed in 6A992.a.1.

6A993 Cameras as follows:

- a. Cameras that meet the criteria of Note 3 to 6A003.b.4.
- b. Not used;

6A994 Optics as follows:

- a. Optical filters:
  1. For wavelengths longer than 250 nm, comprised of multi-layer optical coatings and having either of the following:

- a. Bandwidths equal to or less than 1 nm Full Width Half Intensity (FWHI) and peak transmission of 90 % or more; or
- b. Bandwidths equal to or less than 0,1 nm FWHI and peak transmission of 50 % or more;

Note: 6A994 does not control optical filters with fixed air gaps or Lyot-type filters.

- 2. For wavelengths longer than 250 nm, and having all of the following:
  - a. Tunable over a spectral range of 500 nm or more;
  - b. Instantaneous optical bandpass of 1.25 nm or less;
  - c. Wavelength resettable within 0.1 ms to an accuracy of 1 nm or better within the tunable spectral range; and
  - d. A single peak transmission of 91 % or more;
- 3. Optical opacity switches (filters) with a field of view of 30° or wider and a response time equal to or less than 1 ns;
- b. “Fluoride fibre” cable, or optical fibres therefor, having an attenuation of less than 4 dB/km in the wavelength range exceeding 1,000 nm but not exceeding 3,000 nm.

Technical Note: For the purpose of 6A994.b “Fluoride fibres” are fibres manufactured from bulk fluoride compounds.

6A995 “Lasers” as follows:

- a. Carbon dioxide (CO<sub>2</sub>) “lasers” having any of the following:
  - 1. A CW output power exceeding 10 kW;
  - 2. A pulsed output with a “pulse duration” exceeding 10 µs; and
    - a. An average output power exceeding 10 kW; or
    - b. A pulsed “peak power” exceeding 100 kW; or
  - 3. A pulsed output with a “pulse duration” equal to or less than 10 µs; and
    - a. A pulse energy exceeding 5 J per pulse and “peak power” exceeding 2.5 kW; or
    - b. An average output power exceeding 2.5 kW;
- b. Semiconductor lasers, as follows:

1. Individual, single-transverse mode semiconductor “lasers” having:
  - a. An average output power exceeding 100 mW; or
  - b. A wavelength exceeding 1,050 nm;
2. Individual, multiple-transverse mode semiconductor “lasers”, or arrays of individual semiconductor “lasers”, having a wavelength exceeding 1,050 nm;
- c. Ruby “lasers” having an output energy exceeding 20 J per pulse;
- d. Non-“tunable” “pulsed lasers” having an output wavelength exceeding 975 nm but not exceeding 1,150 nm and having any of the following:
  1. A “pulse duration” equal to or exceeding 1 ns but not exceeding 1  $\mu$ s, and having any of the following:
    - a. A single transverse mode output and having any of the following:
      1. A “wall-plug efficiency” exceeding 12 % and an “average output power” exceeding 10 W and capable of operating at a pulse repetition frequency greater than 1 kHz; or
      2. An “average output power” exceeding 20 W; or
    - b. A multiple transverse mode output and having any of the following:
      1. A “wall-plug efficiency” exceeding 18 % and an “average output power” exceeding 30W;
      2. A “peak power” exceeding 200 MW; or
      3. An “average output power” exceeding 50 W; or
  2. A “pulse duration” exceeding 1  $\mu$ s and having any of the following:
    - a. A single transverse mode output and having any of the following:
      1. A “wall-plug efficiency” exceeding 12 % and an “average output power” exceeding 10 W and capable of operating at a pulse repetition frequency greater than 1 kHz; or
      2. An “average output power” exceeding 20 W; or
    - b. A multiple transverse mode output and having any of the following:
      1. A “wall-plug efficiency” exceeding 18 % and an “average output power” exceeding 30 W; or
      2. An “average output power” exceeding 500 W;

- e. Non-“tunable” continuous wave “(CW) lasers”, having an output wavelength exceeding 975 nm but not exceeding 1,150 nm and having any of the following:
  - 1. A single transverse mode output and having any of the following:
    - a. A “wall-plug efficiency” exceeding 12 % and an “average output power” exceeding 10 W and capable of operating at a pulse repetition frequency greater than 1 kHz; or
    - b. An “average output power” exceeding 50 W; or
  - 2. A multiple transverse mode output and having any of the following:
    - a. A “wall-plug efficiency” exceeding 18 % and an “average output power” exceeding 30 W; or
    - b. An “average output power” exceeding 500 W;

Note: 6A995.e.2.b does not control multiple transverse mode, industrial “lasers” with output power less than or equal to 2 kW with a total mass greater than 1,200kg. For the purpose of this note, total mass includes all components required to operate the “laser”, e.g., “laser”, power supply, heat exchanger, but excludes external optics for beam conditioning and/or delivery.

- f. Non-“tunable” “lasers”, having a wavelength exceeding 1,400 nm, but not exceeding 1,555 nm and having any of the following:
  - 1. An output energy exceeding 100 mJ per pulse and a pulsed “peak power” exceeding 1 W; or
  - 2. An average or CW output power exceeding 1 W;
- g. Free electron “lasers”.

Technical Note: For the purpose of 6A995 “Wall-plug efficiency” is defined as the ratio of “laser” output power (or “average output power”) to total electrical input power required to operate the “laser”, including the power supply/conditioning and thermal conditioning/heat exchanger.

6A996 “Magnetometers”, “Superconductive” electromagnetic sensors, and specially designed components therefor, as follows:

- a. “Magnetometers”, other than those specified in the CML or in Regulation (EU) 2021/821, having a “sensitivity” lower (better) than 1.0 nT (rms) per square root Hz.

Technical Note: For the purposes of 6A996.a, “sensitivity” (noise level) is the root mean square of the device-limited noise floor which is the lowest signal that can be measured.

- b. “Superconductive” electromagnetic sensors, components manufactured from “superconductive” materials:
  1. Designed for operation at temperatures below the “critical temperature” of at least one of their “superconductive” constituents (including Josephson effect devices or “superconductive” quantum interference devices (SQUIDS));
  2. Designed for sensing electromagnetic field variations at frequencies of 1 KHz or less; and
  3. Having any of the following characteristics:
    - a. Incorporating thin-film SQUIDS with a minimum feature size of less than 2  $\mu\text{m}$  and with associated input and output coupling circuits;
    - b. Designed to operate with a magnetic field slew rate exceeding  $1 \times 10^6$  magnetic flux quanta per second;
    - c. Designed to function without magnetic shielding in the earth’s ambient magnetic field; or
    - d. Having a temperature coefficient less (smaller) than 0,1 magnetic flux quantum/K.

6A997 Gravity meters (gravimeters) for ground use, other than those specified in the CML or in Regulation (EU) 2021/821, as follows:

- a. Having a static accuracy of less (better) than 100  $\mu\text{Gal}$ ; or
- b. Being of the quartz element (Worden) type.

6A998 Radar systems, equipment and major components, other than those specified in the CML or in Regulation (EU) 2021/821, and specially designed components therefor, as follows:

- a. Airborne radar equipment, other than those specified in the CML or in Regulation (EU) 2021/821, and specially designed components therefor.
- b. “Space-qualified” “laser” radar or Light Detection and Ranging (LIDAR) equipment specially designed for surveying or for meteorological observation.
- c. Millimeter wave enhanced vision radar imaging systems specially designed for rotary wing aircraft and having all of the following:
  1. Operates at a frequency of 94 GHz;

2. An average output power of less than 20 mW;
3. Radar beam width of 1 degree; and
4. Operating range equal to or greater than 1,500 m.

6A999 Specific processing equipment, as follows:

- a. Seismic detection equipment not controlled by 6A999.c.
- b. Radiation hardened TV cameras, other than those specified in the CML or in Regulation (EU) 2021/821.
- c. Seismic intrusion detection systems that detect, classify and determine the bearing on the source of a detected signal.

6B995 Equipment, including tools, dies, fixtures or gauges, and other specially designed components and accessories therefor, specially designed or modified for any of the following:

- a. For the manufacture or inspection of:
  1. Free electron “laser” magnet wigglers;
  2. Free electron “laser” photo injectors;
- b. For the adjustment, to required tolerances, of the longitudinal magnetic field of free electron “lasers”.

6C992 Optical sensing fibres that are modified structurally to have a “beat length” of less than 500 mm (high birefringence) or optical sensor materials not described in 6C002.b<sup>1</sup> and having a zinc content of equal to or more than 6 % by “mole fraction.”

Technical Note: For the purpose of 6C992:

- 1) “Mole fraction” is defined as the ratio of moles of ZnTe to the sum of the moles of CdTe and ZnTe present in the crystal.
- 2) “Beat length” is the distance over which two orthogonally polarised signals, initially in phase, must pass in order to achieve a 2 Pi radian(s) phase difference.

6C994 Optical materials, as follows:

- a. Low optical absorption materials, as follows:
  1. Bulk fluoride compounds containing ingredients with a purity of 99.999 % or better; or

Note: 6C994.a.1 controls fluorides of zirconium or aluminum and variants.

2. Bulk fluoride glass made from compounds controlled by 6C004.e.1;

- b. “Optical fibre preforms” made from bulk fluoride compounds containing ingredients with a purity of 99,999 % or better, “specially designed” for the manufacture of “fluoride fibres” controlled by 6A994.b.

Technical Note: For the purpose of 6C994:

- 1) “Fluoride fibres” are fibres manufactured from bulk fluoride compounds.
- 2) “Optical fibre preforms” are bars, ingots, or rods of glass, plastic or other materials that have been specially processed for use in fabricating optical fibres. The characteristics of the preform determine the basic parameters of the resultant drawn optical fibres.

6D991 “Software”, other than those specified in the CML or in Regulation (EU) 2021/821, specially designed for the “development”, “production”, or “use” of goods controlled by 6A002, 6A0031, 6A991, 6A996, 6A997, or 6A998.

6D992 “Software” specially designed for the “development” or “production” of equipment controlled by 6A992, 6A994, or 6A995.

6D993 Other “software”, as follows:

- a. Air Traffic Control (ATC) “software” application “programs” hosted on general purpose computers located at Air Traffic Control centers, and capable of automatically handing over primary radar target data (if not correlated with secondary surveillance radar (SSR) data) from the host ATC center to another ATC center.
- b. “Software” specially designed for seismic intrusion detection systems in 6A999.c.
- c. “Source Code” specially designed for seismic intrusion detection systems in 6A999.c.

6E991 “Technology” for the “development”, “production” or “use” of equipment controlled by 6A991, 6A996, 6A997, 6A998 or 6A999.c.

6E992 “Technology” for the “development” or “production” of equipment, materials or “software” controlled by 6A992, 6A994, or 6A995, 6B995, 6C992, 6C994, or 6D993.

6E993 Other “technology” as follows:

- a. Optical fabrication technologies for serially producing optical components at a rate exceeding 10 m<sup>2</sup> of surface area per year on any single spindle and having all of the following:
  1. Area exceeding 1 m<sup>2</sup>; and



2. Surface figure exceeding  $\lambda/10$  (rms) at the designed wavelength;
- b. “Technology” for optical filters with a bandwidth equal to or less than 10 nm, a field of view (FOV) exceeding 40° and a resolution exceeding 0.75 line pairs per milliradian;
  - c. “Technology” for the “development” or “production” of cameras controlled by 6A993;
  - d. “Technology” required for the “development” or “production” of non-triaxial fluxgate “magnetometers” or non-triaxial fluxgate “magnetometer” systems, having any of the following:
    1. “Sensitivity” lower (better) than 0.05 nT (rms) per square root Hz at frequencies of less than 1 Hz; or
    2. “Sensitivity” lower (better) than  $1 \times 10^{-3}$  nT (rms) per square root Hz at frequencies of 1 Hz or more.
  - e. “Technology” required for the “development” or “production” of infrared up-conversion devices having all of the following:
    1. A response in the wavelength range exceeding 700 nm but not exceeding 1,500 nm; and
    2. A combination of an infrared photodetector, light emitting diode (OLED), and nanocrystal to convert infrared light into visible light.

Technical Note: For the purposes of 6E993, “sensitivity” (or noise level) is the rootmean square of the device-limited noise floor which is the lowest signal that can be measured.

## Category 7 – Navigation and Avionics

7A994 Airborne communication equipment, all "aircraft" inertial navigation systems, and other avionic equipment, including components, other than those specified in the CML or in Regulation (EU) 2021/821.

Note 1: 7A994. does not control headsets or microphones.

Note 2: 7A994. does not control goods for the personal use of the natural persons.

7B994 Other equipment specially designed for the test, inspection, or “production” of navigation and avionics equipment.

7D994 “Software”, other than specified in the CML or in Regulation (EU) 2021/821, for the “development”, “production”, or “use” of navigation, airborne communication and other avionics.

7E994 “Technology”, other than specified in the CML or in Regulation (EU) 2021/821, for the “development”, “production” or “use” of navigation, airborne communication, and other avionics equipment.

## Category 8– Marine

8A992 Vessels, marine systems or equipment, and specially designed components therefor, components and accessories as follows:

- a. Underwater vision systems, as follows:
  - 1. Television systems (comprising camera, lights, monitoring and signal transmission equipment) having a limiting resolution when measured in air of more than 500 lines and specially designed or modified for remote operation with a submersible vehicle; or
  - 2. Underwater television cameras having a limiting resolution when measured in air of more than 700 lines;  
  
Technical Note: Limiting resolution in television is a measure of horizontal resolution usually expressed in terms of the maximum number of lines per picture height discriminated on a test chart, using IEEE Standard 208/1960 or any equivalent standard.
- b. Photographic still cameras specially designed or modified for underwater use, having a film format of 35 mm or larger, and having autofocusing or remote focusing “specially designed” for underwater use;
- c. Stroboscopic light systems, specially designed or modified for underwater use, capable of a light output energy of more than 300 J per flash;
- d. Other underwater camera equipment, other than those specified in the CML or in Regulation (EU) 2021/821;
- e. Not used;
- f. Vessels (surface or underwater), including inflatable boats, and specially designed components therefor, other than those specified in the CML or in Regulation (EU) 2021/821;

Note: 8A992.f does not control vessels on temporary sojourn, used for private transport or for the transport of passengers or goods from or through the customs territory of the Union.

- g. Marine engines (both inboard and outboard) and submarine engines and specially designed components therefor, other than those specified in the CML or in Regulation (EU) 2021/821;
- h. Self-contained underwater breathing apparatus (scuba gear) and accessories therefor, other than those specified in the CML or in Regulation (EU) 2021/821;
- i. Life jackets, inflation cartridges, dive compasses and dive computers;

Note: 8A992.i does not control goods for the personal use of the natural persons.

- j. Underwater lights and propulsion equipment;

Note: 8A992.j does not control goods for the personal use of the natural persons.

- k. Air compressors and filtration system specially designed for filling air cylinders;

8D992 “Software” specially designed or modified for the “development”, “production” or “use” of equipment controlled by 8A992.

8D999 “Software” specially designed for the operation of unmanned submersible vehicles used in the oil and gas industry.

8E992 “Technology” for the “development”, “production” or “use” of equipment controlled by 8A992.

## Category 9 – Aerospace and Propulsion

9A990 Diesel engines, and tractors and specially designed components therefor, other than those specified in the CML or in Regulation (EU) 2021/821.

- a. Diesel engines, other than those specified in the CML or in Regulation(EU) 2021/821, for trucks, tractors, and automotive applications, having an overall power output of 298kW or more.
- b. Off highway wheel tractors of carriage capacity 9 t or more; and major components and accessories, other than those specified in the CML or in Regulation(EU) 2021/821.
- c. Road tractors for semi-trailers, with single or tandem rear axles rated for 9 t per axel or more and specially designed major components.

Note: 9A990.b and 9A990.c do not control vehicles on temporary sojourn, used for private transport or for the transport of passengers or goods from or through the customs territory of the Union.

9A991 Gas turbine engines and components, other than those specified in the CML or in Regulation (EU) 2021/821.

- a. Not used.
- b. Not used.
- c. Aero gas turbine engines and components specially designed therefor.  
Note: 9A991.c does not control aero gas turbine engines that are destined for use in civil “aircraft” and that have been in use in bona fide civil “aircraft” for more than eight years.
- d. Not used.
- e. Pressurised aircraft breathing equipment components specially designed therefor, other than those specified in the CML or in Regulation (EU) 2021/821.

9A992 Complete canopies, harnesses, and platforms and electronic release mechanisms therefor, except such types as are in normal sporting use.

9B990 Vibration test equipment and specially designed components, other than those specified in the CML or in Regulation (EU) 2021/821.

Note: 9B990 controls only equipment for the “development” or “production”. It does not control condition monitoring systems.

9B991 Specially designed “equipment”, tooling or fixtures for manufacturing or measuring gas turbine blades, vanes or tip shroud castings, as follows:

- a. Automated equipment using non-mechanical methods for measuring airfoil wall thickness;
- b. Tooling, fixtures or measuring equipment for the “laser”, water jet or ECM/EDM hole drilling processes controlled by 9E003.c;

- c. Ceramic core leaching equipment;
- d. Ceramic core manufacturing equipment or tools;
- e. Ceramic shell wax pattern preparation equipment;
- f. Ceramic shell burn out or firing equipment.

9D990 “Software”, other than those specified in the CML or in Regulation (EU) 2021/821, for the “development” or “production” of equipment controlled by 9A990 or 9B990

9D991 “Software”, for the “development” or “production” of equipment controlled by 9A991 or 9B991.

9E990 “Technology”, other than those specified in the CML or in Regulation(EU) 2021/821, for the “development” or “production” or “use” of equipment controlled by 9A990 or 9B990

9E991 “Technology”, for the “development”, “production” or “use” of equipment controlled by 9A991 or 9B991.

9E993 Other “technology”, not described by 9E003, as follows:

- a. Rotor blade tip clearance control systems employing active compensating casing “technology” limited to a design and development data base; or
  - b. Gas bearing for turbine engine rotor assemblies.’
-